

AQUA 5



AGRICULTURE



Water
Discharge applications

APPLICATIONS

Water delivery lay-flat hose, for irrigation, industrial or waste water.

TECHNICAL DESCRIPTION

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile.


Cover: SBR, black, fabric impression.

Temperature range: -30°C to +80°C.



TRELLEBORG

AQUA 5





AGRICULTURE

AQUA 5



| ID mm | OD mm | WORKING PRESSURE bar | BURSTING PRESSURE bar | WEIGHT kg/m | LENGTH m | ARTICLE NUMBER | STOCK () or min. order m |
|----------|----------|----------------------------|-----------------------------|----------------|-------------|-------------------|---------------------------------|
| 51.0 | 59.0 ±1 | 5 | 15 | 0.94 | 40 | 5503670 | |
| 76.0 | 84.0 ±1 | 5 | 15 | 1.41 | 40 | 5503672 | |
| 90.0 | 98.0 ±1 | 5 | 15 | 1.69 | 40 | 5503673 | |
| 102.0 | 110.0 ±1 | 5 | 15 | 1.86 | 40 | 5503664 | |
| 127.0 | 135.0 ±1 | 5 | 15 | 2.34 | 40 | 5503665 | |
| 152.0 | 161.0 ±1 | 5 | 15 | 3.19 | 40 | 5503666 | |
| 203.0 | 213.0 ±1 | 5 | 15 | 4.22 | 40 | 5503667 | |
| 254.0 | 264.0 ±1 | 5 | 15 | 5.28 | 40 | 5503668 | |
| 305.0 | 316.0 ±1 | 5 | 15 | 6.81 | 40 | 5503669 | |

Tolerance on length: ±1% (ISO 1307 Standard).



TRELLEBORG

WWW.TRELLEBORG.COM/FLUIDHANDLING