

VOLUDEC RED



OIL & GAS

Oil and petroleum/Fuel delivery



APPLICATIONS

For hose reels on road tankers for metered delivery of household and automotive fuel.

ADVANTAGES

A light weight, flexible hose, highly resistant to abrasion.
 Static electricity dissipated by conductive braid.
 Can be supplied ready fitted with swaged gun-metal couplings, sealing caps, or kink resisting spring wire guards.
 Hose assemblies are individually tested and can be supplied with a hydrostatic proof test certificate in accordance with the regulation.

COMPLEMENTARY INFORMATION

Fitted lengths upon request.

TECHNICAL DESCRIPTION

Inner tube	oil and petrol resistant NBR/PVC, black, smooth.
Reinforcement	synthetic textile, braided
Cover	oil and weather resistant NBR/PVC, red, smooth.
Temperature range	-30°C => +55°C
Electrical Properties	built-in-wire for discharge of static electricity.

STANDARD/APPROVAL

EN 1360:2013 type 1.



and embossed: TRELLEBORG - VOLUDEC - EN 1360:2013 - Type 1 - ND - 16bar - M - month/year - batch number - Made in France



OIL & GAS

VOLUDEC RED



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
35.0	48.0	16	48	110	1.11	50	5602765
35.0	48.0	16	48	110	1.11	60	5602766
38.0	52.5	16	48	115	1.39	50	5513199
38.0	52.5	16	48	115	1.39	60	5513200

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

