

VINITRELL G2



FOOD & BEVERAGE

Food industry/Transfer



APPLICATIONS

Specially designed for wine transfers in wine processing industries and for transfer of fresh grapes on the largest diameters. Suction and discharge of any foodstuff including alcohol up to 96% except fatty/oily liquids. Max. vacuum: 0.9 bar.

ADVANTAGES

- An innovative, food grade & extra-smooth tube designed for unrivalled performance and complying with the most stringent European and American requirements for foodstuff handling and unaffected by changes in temperature.
- Optimum organoleptic neutrality, tasteless and odorless to maintain quality.
- The utmost user friendly rubber hose: outstanding flexibility and easy handling thanks to slicking cover, non-marking with weak tractive effort.
- Resistant to cleaning with most common detergents (see our cleaning guideline for details) or with steam at max. 130°C during 30 minutes max.
- Contains no phthalate.

COUPLING/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

COMPLEMENTARY INFORMATION

Please refer to our cleaning guidelines, available upon request and from our website.

TECHNICAL DESCRIPTION

Inner tube	Food-grade special polymer-based SKM, white, smooth
Reinforcement	synthetic textile with embedded steel helix
Cover	special polymer-based, red.
Working temperature	-40°C => +120°C. +130°C peak.

STANDARD/APPROVAL

EU regulations No. 1935/2004, 2023/2006.

EU

FDA regulation No. 21 CFR 177.2600.

FDA

French legislation.

RF

All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.



and embossed: TRELLEBORG - VINITRELL G2 - FDA - WP 10bar - week/year - batch number - Made in France



and embossed: TRELLEBORG - VINITRELL G2 - FDA - WP 6bar - week/year - batch number - Made in France

**FOOD & BEVERAGE****VINITRELL G2**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
38.0	49.5	10	30	80	1.23	20.0	5609457
38.0	49.5	10	30	80	1.23	40.0	5609458
50.0	62.5	10	30	100	1.70	20.0	5609459
50.0	62.5	10	30	100	1.70	40.0	5609460
63.0	75.5	10	30	130	2.08	20.0	5609461
63.0	75.5	10	30	130	2.08	40.0	5609462
70.0	84.0	10	30	140	2.61	20.0	5609463
70.0	84.0	10	30	140	2.61	40.0	5609464
75.0	89.0	10	30	150	2.78	20.0	5609465
75.0	89.0	10	30	150	2.78	40.0	5609466
100.0	116.0	6	18	160	3.77	20.0	5609467
100.0	116.0	6	18	160	3.77	40.0	5609468
125.0	141.0	6	18	170	4.65	20.0	5609469
150.0	166.0	6	18	200	5.63	10.0	5609470
150.0	166.0	6	18	200	5.63	20.0	5609471

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

