

AG 1000 LT



GENERAL INDUSTRY

Exhaust gas hoses



APPLICATIONS

Extraction of exhaust gases and other hot gases from motor vehicles.
For all types of spring recoil exhaust hose reels, exhaust fume extractors and also exhaust rails for moving vehicles.

ADVANTAGES

Extremely low weight and flexibility makes the hose especially suitable for manual handling.
Smooth inside reduces friction losses.
Hose lengths can be connected by screwing them together.

TECHNICAL DESCRIPTION

Inner tube	heat resistant rubberized fabric EPDM polyester, black.
Reinforcement	EPDM-coated steel, black
Working temperature	-40°C => +150°C.
Special Properties	Max. vacuum: 0.4 bar Ø 51 mm, 0.25 bar Ø 76 mm, 0.2 bar Ø 102 mm, 0.15 bar Ø 127 mm, 0.1 bar Ø 152 mm.

COMPLEMENTARY INFORMATION

Delivered in plastic wrapped coils.



	GENERAL INDUSTRY	AG 1000 LT		
ID (MM)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
51.0	65	0.42	10.0	5015842
76.0	95	0.60	10.0	5014503
102.0	110	0.74	10.0	5014504
127.0	130	0.91	10.0	5014505
152.0	140	1.10	10.0	5014506

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

