

AQUA 10 SD



GENERAL INDUSTRY

Water/Suction applications



APPLICATIONS

Water suction and delivery hose used for industrial water, waste water and agricultural equipment.

TECHNICAL DESCRIPTION

Inner tube	SBR, black, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	SBR, black, fabric impression.
Temperature range	-30°C => +80°C

10 SD



TRELLEBORG

AQUA 10 SD





GENERAL INDUSTRY

AQUA 10 SD



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
25.0	35.0	10	30	100	0.71	40	5503700
32.0	42.0	10	30	120	1.01	40	5503701
38.0	48.0	10	30	160	1.19	40	5503702
51.0	63.0	10	30	200	1.72	40	5503703
63.0	75.0	10	30	245	2.23	20	59007854
63.0	75.0	10	30	245	2.23	40	5503704
76.0	88.0	10	30	320	2.57	20	59007855
76.0	88.0	10	30	320	2.57	40	5503705
90.0	103.0	10	30	360	3.36	20	59007856
90.0	103.0	10	30	360	3.36	40	5503706
102.0	116.0	10	30	410	4.05	20	59007857
102.0	116.0	10	30	410	4.05	40	5503695
127.0	143.0	10	30	510	5.82	20	59007858
127.0	143.0	10	30	510	5.82	40	5503696
152.0	169.0	10	30	610	7.66	20	59007859
152.0	169.0	10	30	610	7.66	40	5503697
203.0	225.0	10	30	1000	13.28	20	59007860
203.0	225.0	10	30	1000	13.28	40	5503698
254.0	276.0	10	30	1270	19.17	20	59007861

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

