

SUPERVRAC TAN



BULK MATERIALS HANDLING

Bulk tank truck discharge



APPLICATIONS

Pneumatic transport of bulk abrasive products.
Discharge from road and rail tankers, and delivery to storage bins: cement, sand, lime and also cereals, fertilizers, cattle feed and chemicals (PVC, dye stuffs, granulates, etc.).

ADVANTAGES

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.

TECHNICAL DESCRIPTION

Inner tube	heavy duty abrasion resistant NR, beige, smooth.
Reinforcement	synthetic textile
Cover	weather resistant NR, black, fabric impression.
Temperature range	-30°C => +70°C
Electrical Properties	non conductive tube with built-in wire.





ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
75.0	87.0	7	21	1.72	20	0070661
75.0	87.0	7	21	1.72	40	0125111
89.0	101.0	7	21	1.98	20	0060614
89.0	101.0	7	21	1.98	40	0060615
100.0	112.0	7	21	2.24	20	0070664
100.0	112.0	7	21	2.24	40	0070665
110.0	123.0	7	21	2.50	20	0060617
110.0	123.0	7	21	2.50	40	0060618

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

