

AQUA



AGRICULTURE



Water/Discharge applications

APPLICATIONS

Water delivery hose, for irrigation, industrial or waste water.

3 levels of working pressure available :

- 5 bar (lay-flat hose)
- 10 bar (lay-flat hose from 51mm)
- 20/18 bar for heavy duty usage

TECHNICAL DESCRIPTION

Inner tube	SBR, black, smooth.
Reinforcement	synthetic textile
Cover	SBR, black, fabric impression.
Working temperature	-30°C => +80°C.





ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
25.0	33.0	10	30	0.49	40.0	5503679
25.0	35.0	20	60	0.71	40.0	5503689
32.0	40.0	10	30	0.61	40.0	5503681
32.0	42.0	20	60	0.95	40.0	5503690
38.0	46.0	10	30	0.74	40.0	5503682
38.0	48.0	20	60	1.08	40.0	5503691
51.0	59.0	5	15	0.94	40.0	5503670
51.0	59.0	10	30	0.97	40.0	5503683
51.0	61.0	20	60	1.22	40.0	5503692
63.0	71.0	10	30	1.18	40.0	5503684
63.0	74.0	20	60	1.71	40.0	5503693
76.0	84.0	5	15	1.41	40.0	5503672
76.0	84.0	10	30	1.37	40.0	5503685
76.0	87.0	20	60	1.90	20.0	59007840
76.0	87.0	20	60	1.90	40.0	5503694
80.0	91.0	20	60	2.09	20.0	59007841
80.0	91.0	20	60	2.09	40.0	5503721
90.0	101.0	20	60	2.39	20.0	59007842
90.0	101.0	20	60	2.39	40.0	5503722
102.0	110.0	5	15	1.86	40.0	5503664
102.0	111.0	10	30	2.00	40.0	5503674
102.0	114.0	20	60	2.80	20.0	59007843
102.0	114.0	20	60	2.80	40.0	5503686
127.0	137.0	10	30	2.89	40.0	5503675
152.0	161.0	5	15	3.19	40.0	5503666
152.0	161.0	10	30	3.28	40.0	5503676
152.0	168.0	18	54	9.13	20.0	59007845
152.0	168.0	18	54	9.13	40.0	5503687
203.0	213.0	5	15	4.22	40.0	5503667
203.0	215.0	10	30	6.10	40.0	5503677
203.0	223.0	18	54	14.70	20.0	59007846
254.0	264.0	5	15	5.28	40.0	5503668
305.0	316.0	5	15	6.81	40.0	5503669

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

