

PLUTON ARGON



GENERAL INDUSTRY

Welding hoses



APPLICATIONS

Rubber hose for argon supply in welding application.

ADVANTAGES

Flexible and light weight for easy handling.

Long, safe service life.

The cover is particularly resistant to atmospheric conditions (ozone and hot spots).

Flame resistant in case of flashback.

Very strong textile reinforcement giving high safety factor.

Clear branding showing gas symbol and date of manufacture.

COMPLEMENTARY INFORMATION

ID 6.3mm: 100m standard lengths but we also deliver max 20% of random length (20 and 40m).

TECHNICAL DESCRIPTION

Inner tube	SBR/NR, black, smooth.
Reinforcement	synthetic textile
Cover	SBR, black, smooth.
Working temperature	-30°C => +80°C.

STANDARD/APPROVAL


ISO 3821.

ISO



TRELLEBORG

PLUTON 20 - ISO3821 - ARGON - Ø - 2 MPa (20 bar) - Year





GENERAL INDUSTRY

PLUTON 20 ARGON



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
6.3	12.0	20	60	55	0.13	100.0	5607359
10.0	17.0	20	60	75	0.19	40.0	5600902
20.0	27.5	20	60	90	0.37	20.0	5503092
20.0	27.5	20	60	90	0.37	40.0	5503078

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).