

# BIOVAST RED



## FOOD & BEVERAGE

Food industry/Cleaning



### APPLICATIONS

For cleaning and wash-down operations in food industry including steam cleaning at temperatures up to +165°C. Suitable for reel mounted applications. Also suitable for transfer of aqueous, acidic, alcoholic (up to 70%) or fatty liquid foodstuffs.

### ADVANTAGES

- A tough cleaning hose specially designed for dairies, meat processing, canneries, fish markets, etc.
- Highly flexible.
- Non staining cover.
- Resistant to animal and vegetable fats.
- Contains no phthalate.

### COUPLING/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

### TECHNICAL DESCRIPTION

Inner tube	food grade quality oil resistant NBR, white, smooth.
Reinforcement	synthetic textile
Cover	oil and weather resistant NBR/PVC, red, smooth.
Temperature range	Water: -20°C to +100°C, WP=20bar. Saturated or superheated steam: +165°C/6bar

### STANDARD/APPROVAL

EU regulations No. 1935/2004, 2023/2006.

EU

FDA regulation No. 21 CFR 177.2600.

FDA

French legislation.


RF

All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.

TRELLEBORG



BIOVAST  -  - WP 20 BAR STEAM/VAPEUR 165°C - 6 BAR - Made in France



and embossed: week/year - batch number - 165°C - 6BAR

**FOOD & BEVERAGE****BIOVAST RED**

ID (MM)	OD (MM)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
13.0	23.0	60	65	0.36	20	5513767
13.0	23.0	60	65	0.36	40	5513768
13.0	23.0	60	65	0.36	60	5513769
16.0	26.0	60	85	0.43	20	5513770
16.0	26.0	60	85	0.43	40	5513771
19.0	31.0	60	100	0.59	20	5513772
19.0	31.0	60	100	0.59	40	5513773
25.0	37.0	60	125	0.69	20	5513774
25.0	37.0	60	125	0.69	40	5513775

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

