

PROJECTOR 120 WHITE



CONSTRUCTION & INFRASTRUCTURE

Spraying



APPLICATIONS

For spraying of wet mortar, mixed concrete and other wet products.
Used as a service hose between pump and nozzle in transporting plaster, grout and ready mixed concrete.

ADVANTAGES

High working pressure.
Light weight, flexible and easy to handle.
Abrasion resistant tube.
Non-staining white cover avoids traces on walls and floors.

COMPLEMENTARY INFORMATION

13.3m lengths available on request, min. order is three pieces and by multiple of three.
Other wall thickness and/or bursting pressure on request.

TECHNICAL DESCRIPTION

Reinforcement	synthetic textile
Cover	wear and weather resistant SBR, white, fabric impression.
Temperature range	-30°C => +70°C
Electrical Properties	antistatic tube.
Special Properties	abrasion resistance of tube <40mm3 according to ISO 4649.



TRELLEBORG

PROJECTOR 120 WP 40 BAR 





**CONSTRUCTION &
INFRASTRUCTURE**

PROJECTOR 120 WHITE



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
25.0	39.0	40	120	200	0.85	40	59006807
35.0	49.0	40	120	280	1.13	40	59006808
50.0	68.0	40	120	410	2.22	20	59006809
50.0	68.0	40	120	410	2.22	40	59006810

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

