

# FISH PUMP L



## AQUACULTURE

Farm/Pumping fish



### APPLICATIONS

Used for pumping fish in fish farms and fish processing factories.  
Flat-rolled hose.  
Unique and patented solution for applications requiring long lengths.

### ADVANTAGES

- Flexible hose design providing optimum characteristics for this application.
- Withstands rough handling.
- Without helix for discharge applications.
- Trelleborg's unique, patented solution offering a continuous length of up to 120 m, made possible by innovative junctions.

### COUPLING/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

### COMPLEMENTARY INFORMATION

Other lengths and thickness available on request.

### TECHNICAL DESCRIPTION

Inner tube	wear resistant SBR/NBR, black, smooth.
Reinforcement	synthetic textile.
Cover	weather resistant SBR/NBR, black, fabric impression.
Working temperature	-40°C => +80°C.



and in opposite :



**AGRICULTURE****FISH PUMP L**

ID (MM)	OD (MM)	WALL THICKNESS (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
254.0	261.0	3.5	2	7	3.05	40.0	5010364
254.0	263.0	4.5	3	10	4.06	40.0	2955660
254.0	265.0	5.5	3	10	5.12	40.0	2863290
254.0	263.0	4.5	3	10	4.36	120.0	59021209
254.0	264.0	5.0	3	10	4.83	120.0	59021210
254.0	265.0	5.5	3	10	5.30	120.0	59020900
254.0	266.0	6.0	3	10	5.58	120.0	59021211
254.0	267.0	6.5	3	10	6.06	120.0	59021212
305.0	312.0	3.5	2	7	3.66	30.0	0594432
305.0	312.0	3.5	2	7	3.66	40.0	0208009
305.0	312.0	3.5	3	10	3.83	40.0	2861070
305.0	314.0	4.5	3	10	5.03	40.0	2913530
305.0	316.0	5.5	3	10	6.30	40.0	2911310
305.0	314.0	4.5	3	10	5.28	120.0	59021213
305.0	315.0	5.0	3	10	5.78	120.0	59021214
305.0	316.0	5.5	3	10	6.17	120.0	59021215
305.0	317.0	6.0	3	10	6.91	120.0	59020901
305.0	318.0	6.5	3	10	7.31	120.0	59021216
355.0	362.0	3.5	2	7	4.25	30.0	0594424
355.0	362.0	3.5	2	7	4.25	40.0	0208025
355.0	362.0	3.5	3	10	4.44	40.0	2860840
355.0	364.0	4.5	3	10	5.84	20.0	1300190
355.0	364.0	4.5	3	10	5.84	40.0	2052650
355.0	366.0	5.5	3	10	7.30	40.0	5500653
355.0	364.0	4.5	3	10	6.06	120.0	59021217
355.0	365.0	5.0	3	10	6.71	120.0	59021218
355.0	366.0	5.5	3	10	7.17	120.0	59021219
355.0	367.0	6.0	3	10	8.02	120.0	59020902
355.0	368.0	6.5	3	10	8.48	120.0	59021220
406.0	417.0	5.5	3	10	8.61	120.0	59021221
406.0	418.0	6.0	3	10	9.40	120.0	59020903
406.0	419.0	6.5	3	10	10.11	120.0	59021222
457.0	468.0	5.5	3	10	9.68	120.0	59021223
457.0	469.0	6.0	3	10	10.56	120.0	59020904
457.0	470.0	6.5	3	10	11.78	120.0	59021224
508.0	519.0	5.5	3	10	10.75	120.0	59021225
508.0	520.0	6.0	3	10	11.71	120.0	59020905
508.0	521.0	6.5	3	10	12.99	120.0	59021226

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).