



CHECKER

Standard matting



MECHANICAL, PHYSICAL AND CHEMICAL PROPERTIES

<i>Measured characteristics</i>	Standard	Value	
MECHANICAL			
<i>Rubber compound</i>		synthetic	
<i>Hardness</i>	ASTM D2240	70 ±5	Shore A
<i>Abrasion resistance (5N)</i>	ISO 4649	≤250	mm ³
CHEMICAL RESISTANCE			
<i>Common cleaning products</i>	EN 423	Good	

PROFILE



PATTERN



Checker (MK)

FEATURES

- Non-slip surface.
- Checkered pattern
- Backface: impression
- Thermal and acoustic insulation

ADVANTAGES

- Noise, vibration, and cold propagation reduction
- Good wear and tear resistance
- Excellent walking and standing comfort
- Easy to clean and low maintenance

APPLICATIONS

- Basic flooring for industrial use.

MAINTENANCE RECOMENDATION

Always follow manufacturer warnings and instructions when using any cleaning product.

DIMENSIONS

Code	Stock sit.	Colour	Thickness (mm)	Width (mm)	Length (m)	Weight (kg/m ²)	Pattern	Back face	Dielectric strenght	Marking band	Inner carboard tube Ø mm			
S3203110	stock	●	3	±0.3	1400	±2%	10	±2%	4.06	MK	impression	-	-	80
S3203130	no stock	●	3	±0.3	1000	±2%	15	±2%	4.06	MK	impression	-	-	80

PACKAGING

94/62/EC

Labelling	Self-adhesive label indicating product name, dimensions, area in m ² , nominal weight, and product code to allow product traceability.	LDPE4
Wrapping	Black polyethylene film.	LDPE4

Other colours are available under request.

Depending on the manufacturing process there could be differences in some tonalities of the roll colours.

Colours of the sample kits and catalogues has to be considered as indicative.

Unless typographical error, information and figures of our technical datasheet are based on our experience and laboratory tests according to international standards. This data is intended to be used as a guideline only. Material performance depends on the conditions of use and the final application.