

# AQUA 10 HOT



**GENERAL INDUSTRY**

Water/Discharge applications



## APPLICATIONS

Hot water delivery hose used in industry, construction and agricultural applications.

## TECHNICAL DESCRIPTION


Inner tube	high temperature resistant EPDM, black, smooth.
Reinforcement	synthetic textile
Cover	high temperature resistant EPDM, black, fabric impression.
Temperature range	-30°C => +100°C

**HOT**



**TRELLEBORG**

**AQUA 10 HOT**





GENERAL INDUSTRY

AQUA 10 HOT



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
32.0	42.0	10	30	320	0.73	40	5503649
38.0	48.0	10	30	380	0.85	40	5503650
51.0	63.0	10	30	510	1.37	40	5503651
63.0	75.0	10	30	630	1.68	40	5503652
76.0	89.0	10	30	760	2.22	40	5503653
127.0	141.0	10	30	1270	3.70	40	5503646
152.0	168.0	10	30	1520	5.26	40	5503647

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

