

# SUPERVRAC



## CONSTRUCTION & INFRASTRUCTURE

Bulk tank truck discharge



### APPLICATIONS

Pneumatic transport of bulk abrasive products.  
Discharge from road and rail tankers and delivery to storage bins (cement, sand, limestone, coal, etc.).

### ADVANTAGES

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.
- Static conductive tube.

### COMPLEMENTARY INFORMATION

Can be used in ATEX zones.

### TECHNICAL DESCRIPTION

Inner tube	wear resistant NR, black, smooth.
Reinforcement	synthetic textile
Cover	weather resistant NR, black, fabric impression.
Working temperature	-30°C => +90°C.
Electrical Properties	conductive tube and cover, $R < 10^6 \Omega/m$ .





ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
75.0	88.5	7	21	1.83	20.0	0060675
75.0	88.5	7	21	1.83	40.0	0060674
75.0	93.0	7	21	2.75	20.0	0060189
75.0	93.0	7	21	2.75	40.0	0060193
89.0	101.5	7	21	2.07	20.0	0060682
89.0	101.5	7	21	2.07	40.0	0060683
100.0	112.0	7	21	2.40	20.0	0129701
100.0	112.0	7	21	2.40	40.0	0129702
100.0	118.0	7	21	3.58	20.0	0060194
100.0	118.0	7	21	3.58	40.0	0060195
110.0	123.0	7	21	2.77	20.0	0060684
110.0	123.0	7	21	2.77	40.0	5006696
127.0	144.0	7	21	4.20	20.0	0060685
127.0	144.0	7	21	4.20	40.0	0060686
152.0	169.0	7	21	5.00	20.0	0060689
152.0	169.0	7	21	5.00	40.0	0060690

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

