TECHNICAL PARAMETERS FOR SOLID FUEL LOCAL SPACE HEATERS EU 2015/1185 OF 24. APRIL 2015

Model identifier(s): Scan 41-2	
Indirect heating functionality	No
Direct heat output(kW)	6
Indirect heat output(kW)	N.A

						Emissions from space heating at nominal heat output			
				Preferred fuel	Model	РМ	OGC	СО	NO _x
Fuel			(Only one)		identifier(s)	[X] mg/N	m ₃ (13 %	5 0 ₂)	
Wood logs with moisture o	ontent ← 25	5%		Yes	No	20	92	1221	117
Compressed wood with moisture content < 12%				No	No				
Other woody biomass				No	No				
Anthracite and dry steam coal				No	No				
Hard coke				No	No				
Low temperature coke				No	No				
Bituminous coal				No	No				
Lignite briquettes				No	No				
Peat briquettes				No	No				
Blended fossil fuel briquettes				No	No				
Other fossil fuel				No	No				
Blended biomass and fossil fuel briquettes				No	No				
Other blend of biomass and solid fuel				No	No				
Characteristics when op	erating with	the prefer	red fuel						
Seasonal space heating er	nergy efficie	ncyη _₅ [%]		69					
Energy Efficiency Class			А						
Energy Efficiency Index (EEI)			105						
ltem	Symbol	Value	Unit	lt	ltem		l Va	lue	Unit
Heat output				Use efficie	ency (NCV as re	ceived)			
Nominal heat output	P _{nom}	6	kW	Useful effic nominal hea	ciency at		5	79	%
Minimum heat output (indicative)	P_{min}	N.A.	kW	Useful effic minimum he output (ind	eat n _{+h m}		N	I.A.	%
Auxiliary electricity consumption				Type of he	of heat output/room temperature				select one
At nominal heat output	el _{max}	x,xxx	kW	single stage temperatur	single stage heat output, no room temperature control		[ye	s/no]	
At minimum heat output	el _{min}	x,xxx	kW		two or more manual stages, no room temperature control			s/no]	Yes
In standby mode	el _{sB}	X,XXX	kW	with mechanic thermostat room temperature control			[ye	s/no]	
				with electronic room temperature control			[ye	s/no]	
				with electronic room temperature control plus day timer			[ye	s/no]	
				with electro control plus	with electronic room temperature control plus week timer			s/no]	
					Other control options (multiple select			ossible	
				room tempo presence de	room temperature control, with presence detection		[ye	s/no]	
				open windo	room temperature control, with open window detection			s/no]	
				with distan	with distance control option		[ye	s/no]	
Permanent pilot flame p	ower requir	ement							
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW				1		
Contact details	Name and a	address of tl	he supplier:		Brian Ørum, R&E) Manager, Sca	an A/S, Den	mark	