Model identifier(s): Scan 85										
Indirect heating functionality				No						
Direct heat output(kW)				8						
Indirect heat output(kW)				N.A						
					Emissions from space heating at nominal heat output					
			Preferred				CO CO	NO <sub>x</sub>		
Fuel				<b>fue</b> l (Only one)	Model identifier(s)	[X] mg/Nr			IVO <sub>X</sub>	
Wood logs with moisture content ≤ 25%				Yes	No.			986	89	
Compressed wood with moisture content < 12%				No	No	12	11	300	03	
Other woody biomass				No	No					
Anthracite and dry steam coal				No	No					
Hard coke				No	No					
Low temperature coke				No	No					
Bituminous coal				No	No					
Lignite briquettes				No	No					
Peat briquettes				No	No					
Blended fossil fuel briquettes				No	No					
Other fossil fuel				No	No					
Blended biomass and fossil fuel briquettes				No	No					
Other blend of biomass and solid fuel				No	No					
	110	110								
Characteristics when operating with the preferred fuel  Seasonal space heating energy efficiency η, [%]  68										
Energy Efficiency Class A  Energy Efficiency Index (EEI) 103										
					C	2h.1 V.1 U.5				
Item	Symbol	Value	Unit	Item		Symbol Value		ue	Unit	
Heat output				Use efficiency (NCV as re Useful efficiency at		ceived)				
Nominal heat output	P <sub>nom</sub>	8	kW	nominal heat output		$\eta_{\text{th, nom}}$ 78		3	%	
Minimum heat output (indicative)	$P_{min}$	N.A.	kW	Useful effic minimum he output (indi	$\eta_{\text{th, min}}$ N.A.		۹.	%		
Auxiliary electricity consumption Type of heat output/room temperature control (sele									select one)	
At nominal heat output	el <sub>max</sub>	x,xxx	kW	single stage temperatur	no room [yes/n		'no]			
At minimum heat output	el <sub>min</sub>	x,xxx	kW	two or more manual stages, no room temperature control			[yes/	'no]	Yes	
In standby mode	el <sub>sB</sub>	x,xxx	kW	with mecha temperatur	room [yes/no]		'no]			
				with electro	oerature	e [yes/no]				
				with electro control plus	oerature	[yes/no]				
				with electro control plus	oerature	[yes/no]				
				Other control options (multiple s			ctions po	ssible)		
				room tempe presence de	l, with	[yes/	'no]			
				room tempe open windo	, with [yes/no]		'no]			
				with distan	ce control opti	on	[yes/	no]		
Permanent pilot flame p										
Pilot flame power requirement (if applicable)	P <sub>pilot</sub>	N.A.	kW							
Contact details	Name and address of the supplier:  Contact details  Brian Orum, CEO, Scan A/S, Denmark									