Model identifier(s): ILD	7 ECO, WAR	M 7 ECO							
Indirect heating functionality				No					
Direct heat output(kW)				5,5					
Indirect heat output(kW	/)			N.A					
					Emissions from space heating at nominal heat output				
	al.			Preferred				co CO	NO
Fuel			fue l (Only one)	Model identifier(s)		m ₃ (13 % C		NO _x	
Fuel Wood logs with moisture content ← 25%				Yes	No			9 ₂) 859	99
Compressed wood with moisture content < 12%				No	No	22	09	033	33
Other woody biomass				No	No				
Anthracite and dry steam coal				No	No				
Hard coke				No	No				
Low temperature coke				No	No				
Bituminous coal				No	No				
				No	No				
Lignite briquettes Peat briquettes				No	No				
Blended fossil fuel briquettes				No	No				
Other fossil fuel				No	No				
Blended biomass and fossil fuel briquettes				No	No				
Other blend of biomass and solid fuel				No	No				
Characteristics when operating with the preferred fuel				INO	140				
Seasonal space heating er		•	reuruet	71					
Energy Efficiency Class	iergy erricie	iicy il _s [70]		A+					
Energy Efficiency Class Energy Efficiency Index (EEI)				107					
ltem				Item Symbol			l Valu		1144
	Symbol Value Unit			Use efficiency (NCV as received)			l Vall	je	Unit
Heat output Nominal heat output	P _{nom}	5,5	kW	Useful efficiency at nominal heat output		η _{th, nom}	- 01		%
Minimum heat output (indicative)	P _{min}	N.A.	kW	Useful efficiency at minimum heat output (indicative)		η _{th, min} Ν		۸.	%
Auxiliary electricity consumption				Type of heat output/room temperature control (select one					
At nominal heat output	el _{max}	x,xxx	kW	single stag				elect one	
At minimum heat output	el _{min}	x,xxx	kW	two or mor			no]	Yes	
In standby mode	el _{sB}	x,xxx	kW	with mecha temperatur	t room	[yes/no]			
				with electronic room temperature control			[yes/	no]	
				with electronic room temperature control plus day timer		[yes/	no]		
				with electronic room temperature control plus week timer		[yes/	no]		
				Other control options (multiple selec		ections pos	ssible)		
				room temperature control, with presence detection		[yes/			
				room temperature control, with open window detection		[yes/	no]		
				with distance control option			[yes/	no]	
Permanent pilot flame p	ower requir	ement							
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW			1	1		
Contact details	Name and a	address of t	he supplier:		Brian Ørum, R&I	D Manager, Sca	n A/S, Denma	ark	