Technical parameters for solid fuel local space heaters EU 2015/1186 of 24 April 2015

Model identifier(s): Jøtul F 602 ECO
Indirect heating functionality: no
Direct heat output...(kW) 4,9
Indirect heat output...(kW): N.A

	Preferred	Other	Emissions from space heating at nom			
Fuel	fuel (only	suitable	PM	OGC	СО	NOx
	one):	fuel(s):	(x) mg/Nm ³ (13% O ₂)			
Wood logs with moisture content ≤ 25%	Yes	No	18	46	1133	88
Compressed wood with moisture content < 12%	No	No				
Other woody biomass	No	No				
Non-woody biomass	No	No				
Anthracite and dry steam coal	No	No				
Hard coke	No	No				
Low temperature coke	No	No				
Bituminous coal	No	No				
Lignite briquettes	No	No				
Peat briquettes	No	No				
Blended fossil fuel briquettes	No	No				
Other fossil fuel	No	No				
Blended biomass and fossil fuel briquettes	No	No				
Other blend of biomass and solid fuel	No	No				

Characteristics when operating with the preferred fuel

Seasonal space heating energy efficiency η_s [%]: 71

Energy Efficiency Index (EEI): 107,5

Item	Symbol	Value		Item Symbol Value Unit					
Heat output				Useful efficiency (NCV as received)					
Nominal heat output	P _{nom}	4,9	kW	Useful efficiency at nominal heat η _{th,nom} 81 % output					
Minimum heat output (indicative)	P _{min}	N.A.	kW	Useful efficiency at minimum heat η _{th,min} N.A. % output (indicative)					
Auxiliary electricity	consumption	<u> </u> on		Type of heat output/room temperature control (select one					
At nominal heat output	el _{max}	x,xxx	kW	single stage heat output, no room temperature control [yes/no] Yes					
At minimum heat output	el _{min}	x,xxx	kW	two or more manual stages, no room temperature control [yes/no] No					
In standby mode	el _{SB}	x,xxx	kW	with mechanic thermostat room temperature control [yes/no] No					
				with electronic room temperature control [yes/no] No					
				with electronic room temperature control plus day timer [yes/no] No					
				with electronic room temperature control plus week timer [yes/no] No					
				Other control options (multiple selections possible)					
				room temperature control, with presence detection [yes/no] No					
				room temperature control, with open window detection [yes/no] No					
				with distance control option [yes/no] No					
Permanent pilot	flame powe	er requirem	ent	Sign:					
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW	Espen Auensen, R&D manager					
Contact details	Name and	address of th	ne supplie	r: Jøtul AS, P.O. box 1411, 1602 Fredrikstad, Norway					