Model identifier(s): Scan 1005 CS										
Indirect heating functionality				No						
Direct heat output(kW)				6						
Indirect heat output(kW)				N.A						
						Emissions from space heating				
			Preferred		at nominal heat output					
			fuel Model				0	NO <sub>x</sub>		
Fuel				(Only one)	identifier(s)		n <sub>3</sub> (13 % 0 <sub>2</sub>			
Wood logs with moisture content ← 25%				Yes	No	22	35 8	95	93	
Compressed wood with moisture content < 12%				No	No					
Other woody biomass				No	No					
Anthracite and dry steam coal				No	No					
Hard coke				No	No					
Low temperature coke				No	No					
Bituminous coal				No	No					
Lignite briquettes				No	No					
Peat briquettes				No	No					
Blended fossil fuel briquettes				No	No					
Other fossil fuel				No	No					
Blended biomass and fossil fuel briquettes				No	No					
Other blend of biomass and solid fuel				No	No					
Characteristics when operating with the preferred fuel										
Seasonal space heating energy efficiency $\eta_s$ [%] 72										
Energy Efficiency Class A+										
Energy Efficiency Index (EEI)				109		1				
ltem	Symbol	Value	Unit	Item		Symbol Value		е	Unit	
Heat output				Use efficiency (NCV as re		ceived)				
Nominal heat output	P <sub>nom</sub>	6	kW	Useful efficiency at nominal heat output		$\eta_{\text{th, nom}}$	$\eta_{th, nom}$ 82		%	
Minimum heat output (indicative)	$P_{min}$	N.A.	kW	Useful effic minimum he output (indi	eat	η <sub>th, min</sub>	N.A.		%	
Auxiliary electricity consumption Type of heat output/room temperature control (select									elect one)	
At nominal heat output	el <sub>max</sub>	x,xxx	kW		e heat output,	no room [yes/no]				
At minimum heat output	el <sub>min</sub>	x,xxx	kW	two or more manual stages, no room temperature control			[yes/n	o]	Yes	
In standby mode	el <sub>sB</sub>	x,xxx	kW	with mecha temperatur	nic thermosta e control	t room [yes/no		o]		
				with electro	perature	[yes/no]				
				with electro control plus	perature	[yes/no]				
				with electro control plus	perature	[yes/no]				
				Other cont	nultiple sele	ctions pos	sible)			
				room tempe presence de	l, with	[yes/n	o]			
				room tempe open windo	erature contro w detection	l, with [yes/no]		o]		
				with distan	ce control opti	on	[yes/n	o]		
Permanent pilot flame p										
Pilot flame power requirement (if applicable)	P <sub>pilot</sub>	N.A.	kW			//	2			
Contact details	Name and address of the supplier:  Contact details  Brian Orum, CEO/Scan A/S, Denmark									