DECLARATION OF PERFORMANCE (DOP)

	NO. 90065600-CPR-20220912	
1.	Product Type:	Freestanding stove Scan 65
2.	Type, batch or serial number:	Scan 65 series (Scan 65-1, Scan 65-2, Scan 65-3, Scan 65-4, Scan 65-7, Scan 65-8, Scan 65-9, Scan 65-10)
3.	Intended use of the product:	Heat distribution/room heating Without hot water supply Fuel type: Wood
4.	Name and Address of the manufacturer:	Scan A/S Damsbovej 1 5492 Vissenbjerg
5.	Contact address:	No relevance
6.	AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	System 3
7.	Notified body: Test report no:	DTI NB-No 1235 300-ELAB-2610-EN
8.	Declared performance	
	Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
	Essential characteristics	Performance
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out	A1 Minimum distances in mm: Rear: 50 Sides: 500 Front: 1200 NPD
	Distance to combustible materials	Minimum distances in mm: Rear: 50 Sides: 500 Front: 1200
	Distance to combustible materials Risk of burning fuel falling out	Minimum distances in mm: Rear: 50 Sides: 500 Front: 1200 NPD CO [1174 mg/Nm³] NOx [100 mg/Nm³] OGC [69 mg/Nm³]
	Distance to combustible materials Risk of burning fuel falling out Emission of combustion products	Minimum distances in mm: Rear: 50 Sides: 500 Front: 1200 NPD CO [1174 mg/Nm³] NOx [100 mg/Nm³] OGC [69 mg/Nm³] Dust [14 mg/Nm³]
	Distance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature	Minimum distances in mm: Rear: 50 Sides: 500 Front: 1200 NPD CO [1174 mg/Nm³] NOx [100 mg/Nm³] OGC [69 mg/Nm³] Dust [14 mg/Nm³] NPD
	Distance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature Electrical safety	Minimum distances in mm: Rear: 50 Sides: 500 Front: 1200 NPD CO [1174 mg/Nm³] NOx [100 mg/Nm³] OGC [69 mg/Nm³] Dust [14 mg/Nm³] NPD NPD
	Distance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature Electrical safety Cleanability	Minimum distances in mm: Rear: 50 Sides: 500 Front: 1200 NPD CO [1174 mg/Nm³] NOx [100 mg/Nm³] OGC [69 mg/Nm³] Dust [14 mg/Nm³] NPD NPD
	Distance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature Electrical safety Cleanability Maximum water operating pressure	Minimum distances in mm: Rear: 50 Sides: 500 Front: 1200 NPD CO [1174 mg/Nm³] NOx [100 mg/Nm³] OGC [69 mg/Nm³] Dust [14 mg/Nm³] NPD NPD NPD NPD
	Pistance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature Electrical safety Cleanability Maximum water operating pressure Flue gas temperature at nominal heat output [EN]	Minimum distances in mm: Rear: 50 Sides: 500 Front: 1200 NPD CO [1174 mg/Nm³] NOx [100 mg/Nm³] OGC [69 mg/Nm³] Dust [14 mg/Nm³] NPD NPD NPD NPD T[249°C]

DECLARATION:

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Brian Steen Ørum (CEO)

Vissenbjerg, 12.09.2022 (Place and date of issue) SCAN

