| Model identifier(s): Warr  | m 15 ECO &  | Ild 15 ECO |                              |   |                                  |   |                         |                 |     |
|--|---|------------|------------------------------|---|----------------------------------|---|-------------------------|-----------------|-----|
| Indirect heating functionality   |   |            |                              | No  |                                  |   |                         |                 |     |
| Direct heat output(kW)   |   |            |                              | 5.5                                       |                                  |   |                         |                 |     |
| Indirect heat output(kW)   |   |            |                              | N.A                                       |                                  |   |                         |                 |     |
|  |   |            |                              | B 6 1                                     |                                  | Emissions from space heating at nominal heat output |                         |                 |     |
|  |   |            | Preferred<br>fuel            | Model                                     | PM                               | OGC   | CO                      | NO <sub>x</sub> |     |
| Fuel   |   |            |                              | (Only one)                                | identifier(s)                    | [X] mg/Nr   | m <sub>3</sub> (13 % (  |                 |     |
| Wood logs with moisture content ← 25%  |   |            |                              | Yes                                       | No                               | 19  | 99                      | 1254            | 95  |
| Compressed wood with moisture content < 12%  |   |            |                              | No  | No                               |   |                         |                 |     |
| Other woody biomass  |   |            |                              | No  | No                               |   |                         |                 |     |
| Anthracite and dry steam coal  |   |            |                              | No  | No                               |   |                         |                 |     |
| Hard coke  |   |            |                              | No  | No                               |   |                         |                 |     |
| Low temperature coke   |   |            |                              | No  | No                               |   |                         |                 |     |
| Bituminous coal  |   |            |                              | No  | No                               |   |                         |                 |     |
| Lignite briquettes   |   |            |                              | No  | No                               |   |                         |                 |     |
| Peat briquettes  |   |            |                              | No  | No                               |   |                         |                 |     |
| Blended fossil fuel briquettes   |   |            |                              | No  | No                               |   |                         |                 |     |
| Other fossil fuel  |   |            |                              | No  | No                               |   |                         |                 |     |
| Blended biomass and fossil fuel briquettes   |   |            |                              | No  | No                               |   |                         |                 |     |
| Other blend of biomass and solid fuel  |   |            |                              | No  | No                               |   |                         |                 |     |
| Characteristics when op  |   |            |                              |   |                                  |   |                         |                 |     |
| Seasonal space heating energy efficiency $\eta_s$ [%] 68                                       |   |            |                              |   |                                  |   |                         |                 |     |
| Energy Efficiency Class  |   |            |                              | Α   |                                  |   |                         |                 |     |
| Energy Efficiency Index (EEI)  |   |            |                              | 102                                       |                                  |   |                         |                 |     |
| ltem   | Symbol  | Value      | Unit                         | lt lt                                     | Symbol Value                     |   | ue                      | Unit            |     |
| Heat output  |   |            |                              | <b>Use efficiency</b> (NCV as re          |                                  | ceived)   |                         |                 |     |
| Nominal heat output  | P <sub>nom</sub>  | 5.5        | kW                           | Useful efficiency at nominal heat output  |                                  | $\eta_{\text{th, nom}}$                             | η <sub>th, nom</sub> 77 |                 | %   |
| Minimum heat output (indicative)   | P <sub>min</sub>  | N.A.       | kW                           | Useful effic<br>minimum he<br>output (ind | eat                              | $\eta_{\text{th, min}}$                             | N.A.                    |                 | %   |
| Auxiliary electricity cons   | Type of heat output/room temperature control (select one) |            |                              |   |                                  |   |                         |                 |     |
| At nominal heat output   | el <sub>max</sub>   | x,xxx      | kW                           | single stag<br>temperatur                 | no room [yes/no                  |   | İ                       | ĺ               |     |
| At minimum heat output   | el <sub>min</sub>   | x,xxx      | kW                           | two or more                               | e manual stage<br>erature contro | s, no<br>[yes/                                      |                         | /no]            | Yes |
| In standby mode  | el <sub>sB</sub>  | x,xxx      | kW                           | with mecha<br>temperatur                  | nic thermosta<br>e control       | t room [yes   |                         | /no]            |     |
|  |   |            |                              | with electro                              | perature                         | [yes/no]  |                         |                 |     |
|  |   |            |                              | with electro<br>control plus              | perature                         | ature [yes/no]                                      |                         |                 |     |
|  |   |            |                              | with electro<br>control plus              | perature                         | [yes/no]  |                         |                 |     |
|  |   |            |                              | Other cont                                | nultiple sele                    | ections po  | ssible)                 |                 |     |
|  |   |            |                              | room tempe<br>presence d                  | l, with                          | [yes/   | /no]                    |                 |     |
|  |   |            |                              | room tempo<br>open windo                  | erature contro<br>w detection    | l, with   | with [yes/no]           |                 |     |
|  |   |            | with distance control option |   |                                  | [yes/   | /no]                    |                 |     |
| Permanent pilot flame p  |   |            |                              |   |                                  |   |                         |                 |     |
| Pilot flame power requirement (if applicable)  | P <sub>pilot</sub>  | N.A.       | kW<br>                       |   |                                  |   |                         |                 |     |
| Name and address of the supplier:  Contact details  Brian Ørum, R&D Manager, Scan A/S, Denmark |   |            |                              |   |                                  |   |                         |                 |     |
|  |   |            |                              |   |                                  |   |                         |                 |     |