Indirect heating functionality No	Model identifier(s): Scar	ı 65								
Indirect heat output(kW)					No					
Preferred Fuel Model Contyonal Model	Direct heat output(kW)				6					
Fuel	Indirect heat output(kW)				N.A					
Preferred Value Preferred Value Preferred Value Preferred Value Val										
No										NO.,
Wood logs with moisture content < 25%	Fuel									X
Other woody biomass No No No No Anthractie and dry steam coal No No <t< td=""><td colspan="4"></td><td>Yes</td><td>No</td><td></td><td></td><td>-</td><td>100</td></t<>					Yes	No			-	100
Anthracite and dry steam coal					No	No				
Hard coke Low temperature coke No No No No No No Reat briquettes No No No No Reat briquettes No No No No Reat briquettes No No No No Reat briquettes No No No No Reat briquettes No No No No Reat briquettes No No No No Reat briquettes No No No No No Reat briquettes No No No No No Reat briquettes No N	•				No	No				
Description No No No No No No No	·				No	No				
Bituminous coal Lignite briquettes No No No No Peat briquettes No No No No No Peat briquettes No No No No No Dither fossil fuel briquettes No No No No Dither fossil fuel briquettes No	·				No	No				
Lignite briquettes	Low temperature coke				No	No				
Peat briquettes No	Bituminous coal				No	No				
Blended fossil fuel briquettes No No No No O Blended biomass and fossil fuel briquettes No No No No O Ro No No No O Ro No	Lignite briquettes				No	No				
Other fossil fuel No No <td colspan="4">Peat briquettes</td> <td>No</td> <td>No</td> <td></td> <td></td> <td></td> <td></td>	Peat briquettes				No	No				
Blended biomass and fossit fuel briquettes No	Blended fossil fuel briquettes				No	No				
Other blend of biomass and solid fuel Characteristics when operating with the preferred fuel Seasonal space heating energy efficiency n, [%] Energy Efficiency Index (EEI) Item Symbol Value Unit Heat output Nominal heat output Prom 6 kW Useful efficiency at minimum heat output (indicative) Auxiliary electricity consumption At mominal heat output elmon xxxxxx kW Single stage heat output, no room temperature control In standby mode elso xxxxx kW with mechanic thermostat room temperature control In standby mode elso ymple with electronic room temperature control In standby mode elso ymple with electronic room temperature control (ses/nol) In standby mode elso ymple ym	Other fossil fuel				No	No				
Characteristics when operating with the preferred fuel Seasonal space heating energy efficiency \(\text{\begin{align*}{l} \) Energy Efficiency (Index (EEI) \) Item Symbol Value Unit Heat output Nominal heat output \(\text{\begin{align*}{l} \) Nominal heat output \(\text{\begin{align*}{l} \) Minimum heat output \(\text{\begin{align*}{l} \) Minimum heat output \(\text{\begin{align*}{l} \) Auxiliary electricity consumption At nominal heat output \(\text{\begin{align*}{l} \) At minimum heat output \(\text{\begin{align*}{l} \) At minimum heat output \(\text{\begin{align*}{l} \) Align* \(\text{\begin{align*}{l} \) At minimum heat output \(\text{\begin{align*}{l} \) At	Blended biomass and fossil fuel briquettes				No	No				
Seasonal space heating energy efficiency \(\text{n}_{i} \) \(\text	Other blend of biomass and solid fuel				No	No				
Energy Efficiency Class Energy Efficiency Index (EEI) Item Symbol Value Unit Heat output Nominal heat output Proon 6 kW Observed Indicative) Minimum heat output (indicative) At nominal heat output elmox xxxxx kW Instandby mode In standby	Characteristics when operating with the preferred fuel									
Energy Efficiency Index (EEI) 109	Seasonal space heating er	nergy efficie	ncy η _s [%]		72					
Item Symbol Value Unit Item Symbol Value Unit Heat output	Energy Efficiency Class				Α+					
Use efficiency (NCV as received)	Energy Efficiency Index (EEI)				109					
Nominal heat output	ltem	Symbol	Value	Unit	lt.	Symbol Value		ue	Unit	
Minimum heat output (indicative) Minimum heat output (indicative) Pmin N.A. kW Useful efficiency at minimum heat output (indicative) Type of heat output/room temperature control (select one) single stage heat output, no room temperature control very feminimum heat output elmin x,xxxx kW single stage heat output, no room temperature control very feminimum heat output elmin x,xxxx kW with mechanic thermostat room temperature control very feminimum heat output elmin x,xxxx kW with mechanic thermostat room temperature control very feminimum heat output elmin x,xxxx kW with electronic room temperature control very feminimum heat output elmin x,xxxx kW with electronic room temperature control very feminimum heat output elmin x,xxxx kW with electronic room temperature control very feminimum heat output elmin x,xxxx kW with electronic room temperature control very feminimum heat output elmin x,xxxx kW with electronic room temperature control very feminimum heat output elmin x,xxxx kW with electronic room temperature control very feminimum heat output elmin x,xxxx kW with electronic room temperature control very feminimum heat output, indicative) Type of heat output/room temperature control (select one) single stage heat output, no room temperature control very feminimum heat output, indicative) Type of heat output/room temperature control (select one) with electronic room temperature control very feminimum heat output feminimum heat output (select one) Type of heat output/room temperature control (select one) very feminimum heat output (select one) Type of heat output/room temperature control (select one) with electronic room temperature control (select one) single stage heat output, indicative) Type of heat output/room temperature control (select one) single stage heat output, indicative) Type of heat output/room temperature control (selectone) inversion temperature control (selectone) inversion temperature control very fe	Heat output						ceived)			
Auxiliary electricity consumption At nominal heat output el min x.xxx kW single stage heat output, no room [yes/no] At minimum heat output el min x.xxx kW single stage heat output, no room [yes/no] At minimum heat output el min x.xxx kW two or more manual stages, no room temperature control [yes/no] In standby mode el sa x.xxx kW with mechanic thermosat room [yes/no] with electronic room temperature [yes/no] other control options (multiple selections possible) room temperature control, with [yes/no] room temperature control, with open window detection [yes/no] Permanent pilot flame power requirement Pilot flame power requirement Pilot flame power requirement Name and address of the supplier: Type of heat output, no room temperature control (select one) single stage heat output, no room [yes/no] Yes Type of heat output, no room [yes/no] To more manual stages, no [yes/no] Other control options (multiple selections possible) To com temperature control, with [yes/no] To com temperature control option [yes/no] To com temperature control option Type of heat output, no room Type of heat output, no room In com temperature control option Type of heat output, no room Type of heat output, no room To com temperature control Type of heat output, no room To com temperature control Type of heat output, no room Type of heat output, no room Type	Nominal heat output	P_{nom}	6	kW			η _{th, nom} 82		2	%
At nominal heat output el_max x,xxx kW single stage heat output, no room temperature control [yes/no] Yes In standby mode el_sB x,xxx kW with mechanic thermostat room temperature control [yes/no]		P_{min}	N.A.	kW	minimum he	η _{th, min}	N.A.		%	
At minimum heat output	Auxiliary electricity cons	Type of heat output/room temperature control (select one)								
In standby mode In standby mode el_{SB} x,xxx kW with mechanic thermostat room temperature control [yes/no]	At nominal heat output	el _{max}	x,xxx	kW	single stage temperatur	no room [yes/no		/no]		
temperature control [yes/no] with electronic room temperature [yes/no] with electronic room temperature control [yes/no] with electronic room temperature control plus day timer with electronic room temperature [yes/no] with electronic room temperature control plus week timer Other control options (multiple selections possible) room temperature control, with presence detection room temperature control, with open window detection with distance control option [yes/no] Permanent pilot flame power requirement Pilot flame power requirement Name and address of the supplier:	At minimum heat output	el _{min}	x,xxx	kW	two or more	s, no [yes/		/no]	Yes	
control with electronic room temperature control plus day timer with electronic room temperature control plus week timer With electronic room temperature control plus week timer Other control options (multiple selections possible) room temperature control, with presence detection room temperature control, with open window detection with distance control option [yes/no] Permanent pilot flame power requirement Pilot flame power requirement (if applicable) Name and address of the supplier:	In standby mode	el _{sB}	x,xxx	kW		room [yes/no]		/no]		
control plus day timer with electronic room temperature control plus week timer Other control options (multiple selections possible) room temperature control, with presence detection room temperature control, with open window detection room temperature control, with open window detection with distance control option [yes/no] Permanent pilot flame power requirement Pilot flame power requirement Name and address of the supplier:						perature	[yes/no]			
Control plus week timer Lyes/IIII					with electro control plus	perature	[yes/no]			
room temperature control, with presence detection room temperature control, with presence detection room temperature control, with open window detection with distance control option [yes/no] with distance control option [yes/no] with distance control option [yes/no] N.A. kW Name and address of the supplier:					with electro control plus	perature	[yes/no]			
presence detection [yes/no] room temperature control, with open window detection [yes/no] with distance control option [yes/no] Permanent pilot flame power requirement Pilot flame power requirement (if applicable) P pilot N.A. kW Name and address of the supplier:					Other cont	nultiple sele	ections po	ssible)		
Permanent pilot flame power requirement Pilot flame power requirement (if applicable) N.A. kW Name and address of the supplier:					room temp presence d	l, with	[yes,	/no]		
Permanent pilot flame power requirement Pilot flame power requirement (if applicable) P pilot N.A. kW Name and address of the supplier:					room temp open windo	l, with	with [yes/no]			
Pilot flame power requirement (if applicable) P _{pilot} N.A. kW Name and address of the supplier:	Decreased ailet flows assured to the second			with distan	with distance control option			/no]		
requirement (if applicable) Name and address of the supplier:										
The this	requirement (if applicable)						1	1		
	Contact details	Name and a	address of th	ne supplier:		Brian Ørum	, CEO/Scan A/S	S, Denmark		