



EJ03800

Experience unparalleled ergonomic excellence with our Smart BoardMaster SCN49XP coilnailer! The adjustable long arm and fixed length short arm are designed to minimize worker fatigue and boost productivity. Our BoardMaster absorbs tool recoil, enabling longer, more comfortable work sessions. Benefit from PLC-driven shooting control with precise 10mm distance adjustments and seamless manual mode switching. Toggle between two pre-set firing distances and achieve perfect fastener depth with stepless depth of drive. Ensure perfect alignment with track and laser guides, and maintain correct spacing with adjustable side guides. Enjoy extended battery life with SENCO's 18V battery platform.

APPLICATIONS

Decking, decking soft wood, hardwood flooring, insulation boards, paneling, sheathing, siding, wood-to-wood applications, baseboard, insulation sheathing, boards, wood construction, particle boards

FEATURES




- Telescopic arm
- Programmable PLC
- Adjustable edge guide
- Laser line
- Retractable handle
- Selectable Trigger

TECHNICAL SPECIFICATIONS

Pitch	6 - 8 mm
Wounding type	Flat
Operating temperature	-18 - 49 °C
Oil free	No
Collation type	Wire collated
Alternative collation type	Plastic collated 16mm
Type of nail	Coilnails
Max outerdiameter coil	120 mm
Dimensions	1283 x 314 x 1173 mm
Firing mode	Automatic
Magazine capacity	375 pieces
Shots / second	5
Air inlet size	3/8" female
Air consumption at 60 shots/minute	111 l/m
Operating pressure	5 - 8.3 bar

IDENTIFICATION

FASTENER SPECIFICATIONS

Article Number	EJ03800		
GTIN	8715274245249		
			
	2.1 - 2.87 mm	2.1 - 2.5 mm	2.5 - 2.5 mm



MANUAL RELATED FASTENERS

NAME	FINISH	CODE
Senco cn flat hdg dp ring senc. 2,3x38mm	Hot-Dipped galvanised 3	ELxxASBHR-CN
Senco cn flat hdg dp ring pc 2,1x50mm	Hot-Dipped galvanised 3	SGxxASAC-CN
Senco cn flat hdg dp ring senc. 2,5x65mm	Hot-Dipped galvanised 3	BLxxASBF-CN
Senco cn flat 12mu dp ring jum 2,87x50mm	Zinc plated 12 micron	GLxxAXBF-CN
Senco cn flat 12mu dp ring sen 2,87x65mm	Zinc plated 12 micron	GLxxAXBF-CN