



MAKE IT LAST.

KYOCERA SENCO UK Ltd.  
630 Europa Boulevard  
Gemini Business Park  
Warrington WA5 7YH, United Kingdom  
Tel: +44 (0) 1925 445566  
info@kyocera-senco.co.uk  
www.kyocera-senco.co.uk



## DECLARATION OF PERFORMANCE P10BGA (v0)

Name	P staple 16mm
Article number	P10BGA
GTIN	8715274290065

Intended use/uses and identification of the construction product	
Manufacturer	Kyocera Senco UK Ltd., 630 Europe Boulevard, Warrington WA5 7YH,UK
Intended use	Dowel-type fastener
Unique identification code	P10BGA
DOP No	P10BGA
Designated standard	EN 14592:2008+A1:2012
AVCP	3
NB	1686

Declared performances		
Essential characteristics for: P10BGA		Performance
Characteristic yield moment	$M_{y,k}$	590 Nmm
Characteristic withdrawal parameter	$f_{ax,k}$	4.5 N/mm <sup>2</sup>
Characteristic head pull through parameter	$f_{head,k}$	38.43 N/mm <sup>2</sup>
Characteristic tensile capacity	$f_{tens,k}$	NPD
Durability against corrosion		Stainless Steel A2 (CRC II), SC 1,2 & 3, EN 1995-1-1

$f_{ax,k}$  en  $f_{head,k}$  are tested at a characteristic timber density of 350 kg/m<sup>3</sup>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO UK Ltd by:

Place and date of issue: Warrington,

Lars Aa. Mortensen  
Technical Manager, KYOCERA SENCO EMEA

Additional information		
Staple thickness	$d$	1.4 mm
Staple crown width	$d_h$	25.4 mm
Staple length	$L$	16 mm
Reaction to fire		A1