



MAKE IT LAST.

KYOCERA SENCO Netherlands B.V.
 Pascallaan 88
 8218 NJ Lelystad, The Netherlands
 Tel: +31 (0)320 29 55 75
 info@kyocera-senco.eu
 www.kyocera-senco.eu



DECLARATION OF PERFORMANCE HC59AXBKR-FC (v1)

Name	HC smooth stripnail gas & nail pack 3,1x90mm
Article number	HC59AXBKR-FC
GTIN	8715274165134

Intended use/uses and identification of the construction product	
Manufacturer	Kyocera Senco Netherlands, Pascallaan 88, 8218 NJ Lelystad
Intended use	Dowel-type fastener
Unique identification code	HC59AXBKR-FC
DOP No	HC59AXBKR-FC
Harmonized standard	EN 14592:2008+A1:2012
AVCP	3
NB	1686

Declared performances		
Essential characteristics for: HC59AXBKR-FC		Performance
Characteristic yield moment	$M_{y,k}$	2570 Nmm
Characteristic withdrawal parameter	$f_{ax,k}$	3,1 N/mm ²
Characteristic head pull through parameter	$f_{head,k}$	30,1 N/mm ²
Characteristic tensile capacity	$f_{tens,k}$	NPD
Durability against corrosion		Zinc Plated 12 µm, SC 1 & 2, EN 1995-1-1

fax,k en fhead,k are tested at a characteristic timber density of 350 kg/m³

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO Netherlands B.V. by:

Place and date of issue: Lelystad, 29-05-2025

Lars Aa. Mortensen
 Technical Manager, KYOCERA SENCO EMEA

Additional information		
Nail diameter	d	3,1 mm
Head cross sectional area	d_h	30 mm
Nail length	L	90 mm
Length of point	L_p	4 mm
Coating type	Type	Coating type 3
Reaction to fire		A1