



MAKE IT LAST.

USP CHIPBOARD SCREW COUNTERSUNK HEAD, 6,0X100MM CARBON STEEL STANDARD TENSILE



32108060100

APPLICATIONS

Wood-to-wood applications, composite timbers


TECHNICAL SPECIFICATIONS

Screw head type	Countersunk
Screw recess	Torx 30
Screw thread type	Partly threaded
Wire material	Carbon steel standard tensile
Finish	Clear zinc
Head diameter	12 mm
Point type	Sharp
Screw length	100 - 100 mm
Screw diameter	6 - 6 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274239163
Package quantity	100 pieces
Net weight	1.14 kg

FASTENER SPECIFICATIONS



CE SPECIFICATIONS

CE fastener type	Chipboard screw
Material notification on CE label	Carbon Steel
Protection level in micron	3
Service class	1
Inner threaded diameter	3.65 mm
Threaded/profiled length	60 mm
Characteristic yield moment	8500 Nmm
Characteristic head pull through parameter	14 N/mm ²
Characteristic tensile capacity	10000 N
Torsional ratio	≥1.5
Characteristic torsional resistance	9 Nm
Characteristic torsional strength	9 Nm