

# FLOORING WOOD TO WOOD SCREW 4,2X40MM CARBON STEEL STANDARD TENSILE



## 42RH40MY

### APPLICATIONS

Wood-to-wood applications, subfloor


### TECHNICAL SPECIFICATIONS

Collation type	Plastic collated
Screw head type	Small with 4 nibs
Screw recess	Senco drive 25
Screw thread type	2/3 coarse
Rotations per minute	2300 RPM
Wire material	Carbon steel standard tensile
Finish	Yellow zinc
Head diameter	7 mm
Point type	Type 17 cut point
Point angle	23 °
Screw length	38.8 - 41.2 mm
Screw diameter	4.1 - 4.3 mm

### LOGISTICAL SPECIFICATIONS

GTIN	8715274027838
Package quantity	1000 pieces

### FASTENER SPECIFICATIONS



### CE SPECIFICATIONS

Material notification on CE label	Non-alloy steel
Protection level in micron	3
Service class	1
Inner threaded diameter	2.95 mm
Threaded/profiled length	26 mm
Characteristic yield moment	3283 Nmm
Characteristic head pull through parameter	16 N/mm <sup>2</sup>
Characteristic tensile capacity	4700 N
Torsional ratio	≥ 1,5
Characteristic torsional resistance	1.47 Nm
Characteristic torsional strength	3.47 Nm