

# FLOORING WOOD TO WOOD SCREW 4,2X55MM STAINLESS STEEL AISI 304 (A2)



## 42RH55MS-8014

### APPLICATIONS

Wood-to-wood applications, subfloor


### TECHNICAL SPECIFICATIONS

|                      |                               |
|----------------------|-------------------------------|
| Collation type       | Plastic collated              |
| Screw head type      | Small with 4 nibs             |
| Screw recess         | Senco drive 25                |
| Screw thread type    | 2/3 coarse                    |
| Rotations per minute | 2300 RPM                      |
| Wire material        | Stainless steel AISI 304 (A2) |
| Head diameter        | 7 mm                          |
| Point type           | Type 17 cut point             |
| Pointangle           | 23 °                          |
| Screw length         | 53.8 - 56.2 mm                |
| Screw diameter       | 4.1 - 4.3 mm                  |

### LOGISTICAL SPECIFICATIONS

|                  |               |
|------------------|---------------|
| GTIN             | 8715274054384 |
| Package quantity | 1000 pieces   |
| Net weight       | 3.72 kg       |

### FASTENER SPECIFICATIONS



### CE SPECIFICATIONS

|  |                      |
|--|----------------------|
| Service class                              | 3                    |
| Inner threaded diameter                    | 3.15 mm              |
| Threaded/profiled length                   | 36 mm                |
| Characteristic yield moment                | 2400 Nmm             |
| Characteristic head pull through parameter | 16 N/mm <sup>2</sup> |
| Characteristic tensile capacity            | 3200 N               |
| Torsional ratio                            | ≥ 1,5                |
| Characteristic torsional resistance        | 1.88 Nm              |
| Characteristic torsional strength          | 3.47 Nm              |