



MAKE IT LAST.

KYOCERA SENCO Netherlands B.V.
Pascallaan 88
8218 NJ Lelystad, The Netherlands
Tel: +31 (0)320 29 55 75
info@kyocera-senco.eu
www.kyocera-senco.eu

DECLARATION OF PERFORMANCE SPL-GL26ASBF (v1)



Name	SencoPlus GL ring coilnail 2,8x70mm
Article number	SPL-GL26ASBF
GTIN	8715274139920

Intended use/uses and identification of the construction product	
Manufacturer	Kyocera Senco Netherlands, Pascallaan 88, 8218 NJ Lelystad
Intended use	Dowel-type fastener
Unique identification code	SPL-GL26ASBF
DOP No	SPL-GL26ASBF
Harmonized standard	EN 14592:2008+A1:2012
AVCP	3
NB	1015

Declared performances		
Essential characteristics for: SPL-GL26ASBF		Performance
Characteristic yield moment	$M_{y,k}$	3235 Nmm
Characteristic withdrawal parameter	$f_{ax,k}$	14,75 N/mm ²
Characteristic head pull through parameter	$f_{head,k}$	29,58 N/mm ²
Characteristic tensile capacity	$f_{tens,k}$	NPD
Durability against corrosion		Hot dipped galvanised 55 µm, SC 1,2 & 3, EN 1995-1-1

$f_{ax,k}$ en $f_{head,k}$ are tested at a characteristic timber density of 350 kg/m³

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO Netherlands B.V. by:

Place and date of issue: Lelystad, 26-02-2026

Lars Aa. Mortensen
Technical Manager, KYOCERA SENCO EMEA

Additional information		
Nail diameter	d	2,8 mm
Head diameter	d_h	6,5 mm
Nail length	L	70 mm
Threaded/profiled length	l_g	62 mm
Length of point	L_p	3,7 mm
Coating type	Type	Coating type 3
Reaction to fire		A1