

KYOCERA SENCO UK Ltd.

630 Europa Boulevard Gemini Business Park Warrington WA5 7YH, United Kingdom Tel: +44 (0) 1925 445566 info@kyocera-senco.co.uk www.kyocera-senco.co.uk

DECLARATION OF PERFORMANCE SE15APBV (V0)



Name	Senco cn con. bb dp. ring senc. 2,1x32mm	
Article number	SE15APBV	
GTIN	8715274017655	

Intended use/uses and identification of the construction product			
Manufacturer	Kyocera Senco UK Ltd., 630 Europe Boulevard, Warrington WA5 7YH,UK		
Intended use	Dowel-type fastener		
Unique identification code	SE15APBV		
DOP No	SE15APBV		
Designated standard	EN 14592:2008+A1:2012		
AVCP	3		
NB	1686		

Declared performances					
Essential characteristics for: SE15APBV		Performance			
Characteristic yield moment	$M_{y,k}$	1060 Nmm			
Characteristic withdrawal parameter	$f_{ax,k}$	6.2 N/mm²			
Characteristic head pull through parameter	$f_{\mathit{head},k}$	25 N/mm²			
Characteristic tensile capacity	$f_{\it tens,k}$	NPD			
Durability against corrosion		Carbon steel, SC 1, EN 1995-1-1			

fax,k en fhead,k are tested at a characteristic timber density of 350 kg/m³

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO UK Ltd by:

Place and date of issue: Warrington,

Lars Aa. Mortensen

Technical Manager, KYOCERA SENCO EMEA

Additional information		
Nail diameter	d	2.1 mm
Head cross sectional area	d_h	19 mm
Nail length	L	32 mm
Threaded/profiled length	Ig	22.5 mm
Length of point	Lp	3.3 mm
Coating length	L _h	22.5 mm
Coating type	Туре	Coating type 3
Reaction to fire		A1

