

PRODUCT IDENTIFICATION

Following articles which are sold in the brand name Senco are covered by this Declaration of Performance:



Article number

GL21AABFJ

GL21AXB

GL25APBF

GL27APBF

GL29CABF

GL21AABF

GL25AABF

GL25AXB

GL28APBF

GL27ASBFR

GL21ASDC9005

GL24APBF

GL26APBF

GL29APBF

GL27ASBFJ

The manufacturer declares for:

Round cross-section ring shank nail, diameter 2,87 mm up to 90 mm

Product is in accordance with EN 14592:2008 + A1:2012 "Timber Structures - Dowel-type fasteners - Requirements"

Initial Type Testing was performed to confirm essential characteristic values in accordance to table ZA.1 in EN 14592:2008 + A1:2012. Declared values accompanies with the CE mark in this technical document.

Initial Type Testing is performed by notified body: **1686**

For this product the compliance with the conditions of the Annex ZA in EN 14592 are accomplished.



Treatment:

Bright Basic - Service Class 1

Electro galvanized - Service Class 1

Electro galvanized 12 µm - Service Class 1,2

Hot dipped galvanized 55 µm - Service Class 1, 2, 3

Stainless Steel A2 - Service Class 1, 2, 3

Dimensions

Bright Basic				
Length	Diameter (mm)	Shank type	Length of threaded part (mm)	Length of point (mm)
60mm	2,87	Ring	39	3,7
65mm			44	
70mm			49	
75mm			54	
80mm			57	
85mm			60	
90mm			63	
Electro galvanized / Electro galvanized 12 µm				
Length	Diameter (mm)	Shank type	Length of threaded part (mm)	Length of point (mm)
50mm	2,87	Ring	29	3,7
65mm			44	
90mm			63	

Hot dipped galvanized 55 µm				
Length	Diameter (mm)	Shank type	Length of threaded part (mm)	Length of point (mm)
50mm	2,87	Ring	29	3,7
75mm			54	

Mechanical strenght and stiffness

Bright Basic						
Length	Characteristic yield moment (Nmm)	Characteristic withdrawal parameter (N/mm ²)*,**	Characteristic head pull through parameter (N/mm ²)	Characteristic tensile strenght (N/mm ²)	Coating length (mm)	Head cross sectional (mm ²)
60mm	1950	8,54	27,84	695	46,5	36
65mm					49,5	
70mm					52,5	
75mm					55,5	
80mm					58,5	
90mm					61,5	
Electro galvanized / Electro galvanized 12 µm						
Length	Characteristic yield moment (Nmm)	Characteristic withdrawal parameter (N/mm ²)*,**	Characteristic head pull through parameter (N/mm ²)	Characteristic tensile strenght (N/mm ²)	Coating length (mm)	Head cross sectional (mm ²)
50mm	1950	7,09	27,84	695	37,5	36
65mm					49,5	
90mm					61,5	
Hot dipped galvanized 55 µm						
Length	Characteristic yield moment (Nmm)	Characteristic withdrawal parameter (N/mm ²)*,**	Characteristic head pull through parameter (N/mm ²)	Characteristic tensile strenght (N/mm ²)	Coating length (mm)	Head cross sectional (mm ²)
50mm	1950	8,54	27,84	695	37,5	36
75mm					55,5	

* The withdrawal parameter $f_{ax,k}$ is tested in wood with characteristic density of $\rho_k=350\text{kg/m}^3$

** Coating type 3

System of assessment and verification of constancy of performance for timber fasteners used for structural products is 3.

A Factory Production Control system is established and maintained under responsibilities of the manufacturer:

Name and contact address of the manufacturer

Verpa Senco B.V.

Pascallaan 88

8218 NJ Lelystad, The Netherlands

This declaration of performance is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

June 14, 2013

Lelystad, The Netherlands



Fred van Gerven,
Technical Manager

Document no: VS-CPR-201305-S010