

# FLOORING WOOD TO WOOD SCREW 4,5X75MM CARBON STEEL STANDARD TENSILE



## 45RH75MY

### APPLICATIONS

Subfloor, wood-to-wood applications


### TECHNICAL SPECIFICATIONS

Collation type	Plastic collated
Screw head type	Small with 4 nibs
Screw recess	Senco drive 25
Screw thread type	2/3 coarse
Rotations per minute	2300 RPM
Wire material	Carbon steel standard tensile
Finish	Yellow zinc
Point type	Type 17 cut point
Pointangle	23 °
Screw length	73.5 - 76.5 mm
Screw diameter	4.3 - 4.7 mm

### LOGISTICAL SPECIFICATIONS

GTIN	8715274027937
Package quantity	1000 pieces
Net weight	5.5 kg

### FASTENER SPECIFICATIONS



### CE SPECIFICATIONS

Material notification on CE label	Non-alloy steel
Protection level in micron	3
Service class	1
Inner threaded diameter	3.05 mm
Threaded/profiled length	50 mm
Characteristic yield moment	4300 Nmm
Characteristic head pull through parameter	14 N/mm <sup>2</sup>
Characteristic tensile capacity	7300 N
Torsional ratio	≥ 1,5
Characteristic torsional resistance	1.47 Nm
Characteristic torsional strength	6 Nm