

FLOORING WOOD TO WOOD SCREW 4,2X55MM STAINLESS STEEL AISI 316 (A4)



42R55MX

APPLICATIONS

Wood-to-wood applications, subfloor


TECHNICAL SPECIFICATIONS

| | |
|----------------------|-------------------------------|
| Collation type | Plastic collated |
| Screw head type | Small with 4 nibs |
| Screw recess | Phillips 2 |
| Screw thread type | 2/3 coarse |
| Rotations per minute | 2300 RPM |
| Wire material | Stainless steel AISI 316 (A4) |
| Head diameter | 7 mm |
| Point type | Type 17 cut point |
| Point angle | 23 ° |
| Screw length | 53.8 - 56.2 mm |
| Screw diameter | 4.1 - 4.35 mm |

LOGISTICAL SPECIFICATIONS

| | |
|------------------|---------------|
| GTIN | 8715274059297 |
| Package quantity | 1000 pieces |
| Net weight | 3.79 kg |

FASTENER SPECIFICATIONS



CE SPECIFICATIONS

| | |
|--|----------------------|
| Service class | 3 |
| Inner threaded diameter | 3.15 mm |
| Threaded/profiled length | 36 mm |
| Characteristic yield moment | 2400 Nmm |
| Characteristic head pull through parameter | 16 N/mm ² |
| Characteristic tensile capacity | 3200 N |
| Torsional ratio | ≥ 1,5 |
| Characteristic torsional resistance | 1.88 Nm |
| Characteristic torsional strength | 3.47 Nm |