



WCE0485

The SLP20XP GLN is an air powered glazing brad nailer for fastening indoor glass retaining strips. The 1,2mm (AX) nail is curved and drives covered in the notch, ranging in length from 25mm to 38mm. Place your nails with an interspace of 30cm for the best results. Drive the last one on the strip at max. 8 till 10.5 cm to the end.

APPLICATIONS

Doors and windows

FEATURES

- Comfort grip
- Reload indicator
- Oil-free


TECHNICAL SPECIFICATIONS

Oil free	Yes
Collation type	Glue collated
Type of nail	Brads
Includes case	Yes
Net weight	1.17 kg
Firing mode	Restrictive
Magazine capacity	110 pieces
Air inlet size	1/4" female
Air consumption at 60 shots/minute	54 l/m
Operating pressure	4.8 - 8.3 bar

IDENTIFICATION

Article number	WCE0485
GTIN	8715274044927

FASTENER SPECIFICATIONS



FASTENERS

NAME	FINISH	CODE
AX brad 1,2x25mm	Regular galvanised	AXxxEAAP
AX brad 1,2x25mm		AXxxEGA
AX brad 1,2x30mm		AXxxEGA
AX brad 1,2x35mm	Regular galvanised	AXxxEAAP
AX brad 1,2x25mm	Regular galvanised	AXxxEAAP

ACCESSORIES



NAME	CODE
Air plug 320 compatible 1/4"NPT, male	4000100



NAME	CODE
Air hose kit universal 10m x 6,5mm (i.d.) 10mm (o.d.)	4000650

MATCHING PRODUCTS



NAME	CODE
PC1010, mini compressor	PC1010EU



NAME	CODE
PC1010, mini compressor, 230V	PC1010UK2



NAME	CODE
PC1010, mini compressor, 110V	PC1010UK1



NAME	CODE
AC8305UK 110V, low noise compressor	AFN0028UK