

**42R45MYN****APPLICATIONS**


Wood-to-wood applications, subfloor

**TECHNICAL SPECIFICATIONS**

Collation type	Plastic collated
Screw head type	Small with 4 nibs
Screw recess	Phillips 2
Screw thread type	2/3 coarse
Rotations per minute	2300 RPM
Wire material	Carbon steel standard tensile
Finish	Yellow zinc
Head diameter	7 mm
Point type	Type 17 cut point
Point angle	23 °
Screw length	43.8 - 46.2 mm
Screw diameter	4.1 - 4.3 mm

**LOGISTICAL SPECIFICATIONS**

GTIN	8715274251820
Package quantity	4000 pieces

**FASTENER SPECIFICATIONS**

43.8 - 46.2 mm

4.1 - 4.3 mm

**CE SPECIFICATIONS**

Material notification on CE label	Non-alloy steel
Protection level in micron	3
Service class	1
Inner threaded diameter	2.95 mm
Threaded/profiled length	30 mm
Characteristic yield moment	3283 Nmm
Characteristic head pull through parameter	16 N/mm <sup>2</sup>
Characteristic tensile capacity	4700 N
Torsional ratio	≥ 1,5
Characteristic torsional resistance	1.47 Nm
Characteristic torsional strength	3.47 Nm