



MAKE IT LAST.

KYOCERA SENCO Netherlands B.V.
Pascallaan 88
8218 NJ Lelystad, The Netherlands
Tel: +31 (0)320 29 55 75
info@kyocera-senco.eu
www.kyocera-senco.eu



DECLARATION OF PERFORMANCE SPL-H559AUBXR (v1)

| | |
|----------------|---|
| Name | SencoPlus H6 offset smooth stripnail 3,1x90mm |
| Article number | SPL-H559AUBXR |
| GTIN | 8715274140094 |

| Intended use/uses and identification of the construction product | |
|--|--|
| Manufacturer | Kyocera Senco Netherlands, Pascallaan 88, 8218 NJ Lelystad |
| Intended use | Dowel-type fastener |
| Unique identification code | SPL-H559AUBXR |
| DOP No | SPL-H559AUBXR |
| Harmonized standard | EN 14592:2008+A1:2012 |
| AVCP | 3 |
| NB | 1015 |

| Declared performances | | |
|--|--------------|---|
| Essential characteristics for: SPL-H559AUBXR | | Performance |
| Characteristic yield moment | $M_{y,k}$ | 5270 Nmm |
| Characteristic withdrawal parameter | $f_{ax,k}$ | 3,42 N/mm ² |
| Characteristic head pull through parameter | $f_{head,k}$ | 33,88 N/mm ² |
| Characteristic tensile capacity | $f_{tens,k}$ | NPD |
| Durability against corrosion | | Stainless Steel A4 (CRC III), SC 1,2 & 3, EN 1995-1-1 |

$f_{ax,k}$ en $f_{head,k}$ are tested at a characteristic timber density of 350 kg/m³

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO Netherlands B.V. by:

Place and date of issue: Lelystad, 26-02-2026

Lars Aa. Mortensen
Technical Manager, KYOCERA SENCO EMEA

| Additional information | | |
|------------------------|-------|----------------|
| Nail diameter | d | 3,1 mm |
| Head diameter | d_h | 6,8 mm |
| Nail length | L | 90 mm |
| Coating type | Type | Coating type 3 |
| Reaction to fire | | A1 |