



MAKE IT LAST.

KYOCERA SENCO Netherlands B.V.
Pascallaan 88
8218 NJ Lelystad, The Netherlands
Tel: +31 (0)320 29 55 75
info@kyocera-senco.eu
www.kyocera-senco.eu

DECLARATION OF PERFORMANCE 39A50MP (v4)



| | |
|----------------|---|
| Name | Drywall to wood screw PH2 phosphated 3,9x50mm |
| Article number | 39A50MP |
| GTIN | 8715274010632 |

| Intended use/uses and identification of the construction product | |
|--|--|
| Manufacturer | Kyocera Senco Netherlands, Pascallaan 88, 8218 NJ Lelystad |
| Intended use | Mechanical fastener |
| Unique identification code | 39A50MP |
| DOP No | 39A50MP |
| Harmonized standard | EN 14566:2008+A1:2009 |
| AVCP | 4 |

| Declared performances | |
|--|-------------|
| Essential characteristics for: 39A50MP | Performance |
| Reaction to fire | A1 |
| Flexural strength | Pass |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO Netherlands B.V. by:

Place and date of issue: Lelystad, 27-11-2025

Lars Aa. Mortensen
Technical Manager, KYOCERA SENCO EMEA

| Additional information | | |
|--------------------------|-------|---------|
| Screw diameter | d | 3,9 mm |
| Head diameter | d_h | 8 mm |
| Screw length | L | 50 mm |
| Threaded/profiled length | l_g | 45,5 mm |
| Inner threaded diameter | d_i | 2,65 mm |
| Reaction to fire | | A1 |