



MAKE IT LAST.

KYOCERA SENCO UK Ltd.
630 Europa Boulevard
Gemini Business Park
Warrington WA5 7YH, United Kingdom
Tel: +44 (0) 1925 445566
info@kyocera-senco.co.uk
www.kyocera-senco.co.uk



DECLARATION OF PERFORMANCE SPL-NN24ASBD (v0)

Name	Sencoplus, NN metalconnector ring 4,0x60mm
Article number	SPL-NN24ASBD
GTIN	8715274140261

Intended use/uses and identification of the construction product	
Manufacturer	Kyocera Senco UK Ltd., 630 Europe Boulevard, Warrington WA5 7YH,UK
Intended use	Dowel-type fastener
Unique identification code	SPL-NN24ASBD
DOP No	SPL-NN24ASBD
Designated standard	EN 14592:2008+A1:2012
AVCP	3
NB	1015

Declared performances		
Essential characteristics for: SPL-NN24ASBD		Performance
Characteristic yield moment	$M_{y,k}$	9346 Nmm
Characteristic withdrawal parameter	$f_{ax,k}$	8.14 N/mm ²
Characteristic head pull through parameter	$f_{head,k}$	28.33 N/mm ²
Characteristic tensile capacity	$f_{tens,k}$	NPD
Durability against corrosion		Hot dipped galvanised 55 µm, SC 1,2 & 3, EN 1995-1-1

$f_{ax,k}$ en $f_{head,k}$ are tested at a characteristic timber density of 350 kg/m³

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO UK Ltd by:

Place and date of issue: Warrington,

Lars Aa. Mortensen
Technical Manager, KYOCERA SENCO EMEA

Additional information		
Nail diameter	d	4 mm
Head diameter	d_h	7.3 mm
Head cross sectional area	d_h	50 mm
Nail length	L	60 mm
Threaded/profiled length	l_g	20 mm
Coating type	Type	Coating type 3
Reaction to fire		A1