P70 EVO



Evolution of the original P70 launched in 2009, P70 EVO offers the widest range of semi-professional tools on the market and can be used in all 4 seasons. It has been designed and developed for users who need to maintain high efficiency while saving resources, time and storage space.

ENGINES



B&S 850 E series Gasoline - 190 cc 3.73 Kw Fuel tank 1,0 L



B&S 850 IS series Eletrict starter Gasoline - 190 cc 3,73 Kw Fuel tank 1,0 L



LONCIN LC1P75F Gasoline - 224 cc 4.35 Kw Fuel tank 1,2 L



HONDA GCV200 Gasoline - 166 cc 4.2 Kw Fuel tank 0,91 L

GEAR BOX - SPEED

Front tools: (3+2)





















TECHNICAL FEATURES



TRANSMISSION

Gears and endless screwin oil bath and belt



PTO

Vertical with belt, quick connection system



SLOPE

Optional KIT to work sideways on steep slopes up to 40° (Honda) and 45° (B&S)



HANDLEBAR

Adjustable in height and sideways, reversible handlebar



TRACTION WHEELS

Run flat tyres, tractor profile 15x6,00-6



WEIGHT & DIMENSION 63 Kg

Packaging: 80x57x63 (h) cm Pallet (6 pz.): 90x120x201 (h) cm

ENGINE on SLOPE - Optional kit -





SNOW CHAINS



For pneumatic wheels 15x6,00-6

KIT SWATH



Side courtain for rotary scythe, lenght: 64 cm

IRON WHEELS



Iron extension for wheels Roadway 75 cm

RIDGING PLOUGH



Fixed wings Rear connection



P70 EVO



GRASSLAND MOWER



Rotor: single Cutting: 6 pivoting blades Working width: 63 cm Cutting height: 5 o 8 cm

ROTARY SCYTHE



Cutting: 4 pivoting blades Working width: 64 cm Cutting height: adjustable Swath Kit - optional

CUTTING BAR



Blade movement: patented
Working width: 102 cm
Single floating grass deflector

BELT RAKE



Combs: 7, 4 teeth per comb Belt: single 3,2 cm Working width: 100 cm Double pivoting wheels

SNOW BLADE



Blade: quick connection Sideways adjustable Working width: 85 cm Shockproof rubber system

BRUSH COLLECTOR



Brush: Ø 30 cm + ABS collector Rotation: 113 e 207 RPM Working width: 88 cm Side adjustable

SNOW THROWER



Turbine: double stage Working width: 52 cm Cutting height: adjustable Chimney: side adjustable

ROTAVATOR



Rear connection Cutter: 16 knifes Working width: 55 cm, Ø 32 cm Rear protection casing

DE-THATCHER



With springs Working width: 50 cm Wheels: fix Rear protection casing

TRANSPORT TANK



Capacity: 85 litri
Loading: 75 Kg on flat ground
Tank: galvanized
Discharge system: thorugh leverage

COLLECTOR LDPE



Capacity: 160 litres
Loading: 75 Kg on flat grounds
Platform: metal sheet 57x81x10 cm
Discharge system: through leverage

ECO SPRAYER



Pump: 12 V - 4,1bar Batteries: x2, 12 V - 5 Ah each Tank: 50 + 10 litri

Sprayer lance: with atomizer
Hose: 9 m, hose reel support
Wheels: double pivoting wheels

VACUUM BLOWER



Bag capacity: 185 litri Intake width: 78 cm Fan n. turns: 2600 rpm Hose blower Ø 10x250 cm