

Technical Information Dust Remover non-flammable



Powerful tool to under high pressure remove dust and loose dirt from places which are hard to reach. Dust remover is non-flammable and inodorous and leaves no residue. presto Dust Remover is very user-friendly and has a powerful, directed jetspray.

Quality and properties

- User-friendly
- Very effective
- Non-flammable
- Powerful, directed jetspray
- Leaves no residue
- Inodorous

Physical and chemical data

- **Basis:** 1,2,2,2-Tetrafluoroethane
- **Smell:** Inodorous
- **Relative density at 20°C:** 1.23 g/ml
- **Vapour pressure at 20°C:** 3.5 - 4.5 bar
- **Boiling point:** - 24,8°C
- **VOC-content:** 100% w/w
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
aerosol can, maximum nominal volume 250 ml

Environment and labelling

Environmentally compatible: MOTIP DUPLI is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Labelling: All products of MOTIP DUPLI comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Instruction manuel

Before use, carefully read and observe the warning texts on the label!

Application:

- Bring can to room temperature.
- Operating temperature 5° to 30°C.
- During treatment, the aerosol should be in straight position.
- Repeatedly, briefly press the nozzle.
- When pressure falls (the aerosol feels cold), interrupt the treatment in order to restore the pressure in the aerosol.

Tips for spray painting

Protect the object and the surrounding area from spray mist.
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of: September 18, 2019

This release replaces all eventually earlier issued versions.

Print date: 18.09.2019

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info@de.motipdupli.com