

EU Type Examination Certificate

Date: 2018/06/18

n. **158182501/OE**

Validity:
2023/06/17

This document cancels & replaces the previous one nr. 158162602/OE dated 2016/06/27

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	GRISPORT SpA calzaturificio 31030 CASTELCUCCO (TV) – Via Erega, 1 – ITALIA
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)
Category of PPE:	II : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.
Model	"700603CA4"
Description:	<p><u>design</u>: A (low shoe); <u>fastening system</u>: by means of laces; <u>processing</u>: direct injection; <u>sole</u>: orange rubber marked "TOTAL GRIP HI SRC HRO CROSS OIL RESISTANT" (cod. 030BN/00 – 003/ 78/00); <u>midsole</u>: black foam PU (cod. MPI/001); <u>upper</u>: black/anthracite grey three-dimensional fabric article ANDROID/HMPU/AT488 SPECIAL (cod. AA8/N/A), with lateral inserts made of coated non woven fabric declared thickness 1,4 mm LAV. EST. color TRUE BLACK (cod. PRE/TRBL) and coated non woven fabric in the heel area declared thickness 1,4 mm SINTETICO color TRUE BLACK (cod. PRB/TRBL); <u>tongue</u>: made of the same material of the upper, simple; <u>bellows</u>: black coated fabric article ANDREA SILVIA (cod. ANS/NER) lined; <u>vamp lining</u>: black tnt AITELLE 150 matched to MTP4 and black CHARMEUSE (cod. FCA/NEC); <u>quarter lining</u>: orange three-dimensional fabric AT 488 SPECIAL (cod. A8S/ARA); <u>heel-grip</u>: black microfiber MICROLIM 0,8 SCAMOSCINA (cod. MI8/NER); <u>insole</u>: white multi-layered fabric ZP03/1500 (cod. LC/ZP03) <u>which serves also as perforation resistant insert</u>; <u>removable insock</u>: grey perforated foam material matched with black fabric in contact with the foot, with an aluminium oval stitched onto the lower part of the forepart with antistatic thread, with a red ABS insert in the heel area (cod. FTNAROA); as an alternative to <u>removable insock</u>: black agglomerate material with red foam reinforcement in the heel area, matched with a black/silver fabric in contact with the foot (art. FM126N); <u>toecap</u>: glass fiber article 604 CONTENDER (cod. 604FV); as an alternative to <u>toecap</u>: glass fiber article 604 SAFIT (cod. 604FV).</p> <p><u>Optional interchangeable orthopedic insocks (DGVV 112-191)</u> described by the Customer as below (see also page 2): SECOSOL® by Matthias Hartmann Orthopädie + Sport GmbH (max thickness in the toetip area: 2,93 mm) A) Secosol BASE 9516 incl. EVA-covers Sizes: 35/50 (95161001114100-95164294249459) B) Secosol BASE 9516 incl. TEXTIL-covers Sizes: 35/50 (95161001114100-95164294249459) C) Secosol Complete incl. EVA-covers Sizes: 35/36 – 49/50 (95162201245136-95162201245150) D) Secosol Complete incl. TEXTIL-covers Sizes: 35/36 – 49/50 (95162201247136-95162201247150).</p>



EU Type Examination Certificate

Date: 2018/06/18

n. **158182501/OE**

Validity:
2023/06/17

Technical Standard: **EN ISO 20344:2011** Personal protective equipment – Test methods for footwear
(UNI EN ISO 20344:2012)
EN ISO 20345:2011 Personal protective equipment – Safety footwear
(UNI EN ISO 20345:2012)

Intended use: general industry, engineering industry, agriculture, warehouses, works on trucks, cranes.

Size range: from 35 to 48

Technical File: **DC-9555/E + DC-8932/E**

Test report: **RCT n°352455.02/E + n°364659 + n°3713030**

Functions and performance levels: **basic requirements for safety footwear (SB)** (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which:

SRC = Slip resistance – meets the following requirement:

- surface: ceramic / lubricant: detergent solution;
- surface: steel / lubricant: glycerol.

Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011):

S1 = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, **P** = penetration resistance; **HRO** = resistance to hot contact of the outsole; **HI** = heat insulation of sole complex.

Note: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption).

Marking: on a stitched label and displaying the following information:

 **UNI EN ISO**
20345:2012
05 / 2016
700603CA4 S1+P HRO
HI SRC
XXXXXX
700603c4
42

- **CE Marking**;
- Name of the Manufacturer (on the external side of the footwear);
- designation of the footwear (article code: unique/unambiguous);
- nr. and year of the Standard of reference;
- safety symbols;
- size of the footwear;
- production date (month + year);
- additional information: internal codes.



A) Secosol BASE 9516
incl. EVA-covers
Sizes: 35/50
(95161001114100-
95164294249459)

B) Secosol BASE 9516
incl. TEXTIL-covers
Sizes: 35/50
(95161001114100-
95164294249459)

C) Secosol Complete
incl. EVA-covers
Sizes: 35/36 – 49/50
(95162201245136-
95162201245150)

D) Secosol Complete
incl. TEXTIL-covers
Sizes: 35/36 – 49/50
(95162201247136-
95162201247150)

NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

