Suction cup VL50BX, 1/4"NPT-1/8"NPSF

Article number: 0202732



- Suitable for level adjustment.
- Several short bellows in one lifting device can handle objects with height differences and varying shapes, for example embossed or corrugated plates
- The lifting movement can be used to separate small and thin objects
- Only light weight objects should be handled when the lifting force is parallel to the surface of the object in order to achieve good precision and safe lifting movement
- Volume discounts available for big packs from 30-99 pieces with an even larger discount for big packs of 100 pieces and above

TPE-U

PVC-free recycable material

Technical data

| Description | Unit | Value |
|--------------------------|------|-------------------------|
| Suction cup shape | - | Bellows |
| Suction cup design | - | Round |
| Material | - | TPE |
| Suction cup model | - | BX-P |
| Height (B) | mm | 43.6 |
| Height 2 (D) | mm | 15 |
| Inner diameter (C) | mm | 10 |
| Outer diameter, min. (A) | mm | 50 |
| Fitting size | - | 1/4", 1/8" |
| Fitting option | - | None |
| Fitting style | - | Female/Male |
| Fitting type | - | NPT-thread, NPSF-thread |
| Suction cup model | - | VL50BX TPE-U |

Performance - Lifting forces


| VL50BX TPE-U | Vertical (N) | Parallel (N) |
|--------------|--------------|--------------|
| 50 -kPa | 44 N | |

Material

Name

| Colour | Purple | | | | |
|------------------------|--------|--|--|--|--|
| Temperature, min. °C | 0 | | | | |
| Temperature max. °C | 60 | | | | |
| Hardness °Shore A | 65 | | | | |
| Material resistance | | | | | |
| Alcohol | n/a | | | | |
| Concentrated acids | n/a | | | | |
| Ethanol | n/a | | | | |
| Hydrolysis | n/a | | | | |
| Methanol | n/a | | | | |
| Oil | n/a | | | | |
| Oxidation | n/a | | | | |
| Petrol | n/a | | | | |
| Wear resistance | n/a | | | | |
| Weather and ozone | n/a | | | | |

Dimensional drawings



Values specified in this data sheet are tested at (unless otherwise stated):

- •Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- •Standard atmosphere (101.3 [29.9 inHg] \pm 1.0 kPa [0.3 inHg]).
- •Relative humidity 20-70%.
- •Compressed air quality, DIN ISO 8573-1 class 4.

Accessories

0202158 | Fitting VL D=Ø10, G1/4" - G1/8" 0202164 | Fitting VL D=Ø10, G3/8" - G1/4" 0202166 | Fitting VL D=Ø10, 3/8" NPT - 1/4" NPSF

Spare parts

0202162 | Fitting VL D=Ø10, 1/4" NPT - 1/8" NPSF 0202114 | Suction cup VL50BX