### Datasheet

# Suction cup F75 HNBR, 1/4" NPT female Al, with mesh filter & 10-32 addl. conn.

Article number: 0128159



- Suitable for flat objects.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.

#### **Technical data**

i ooiiiiioai aata		
Description	Unit	Value
Suction cup shape	-	Flat
Application	-	Dry sheet metal, Plastic injection molded parts, Glass handling, High/low temp cup (plastic), Mark Free
Suction cup design	-	Round
Characteristics	-	Dry sheet metal, Plastic injection molded parts, Glass handling, High/low temp cup (plastic), Mark free
Material	-	HNBR
Weight, min.	g	23
Suction cup model	-	F
Volume	cm <sup>3</sup>	20
Height	mm	21
Outer diameter, min.	mm	77
Fitting size	-	1/4"
Fitting option	-	None
Fitting style	-	Female
Fitting type	-	NPT-thread
Suction cup model	-	F75
Movement, vertical max.	mm	3
Curve radius, min.	mm	150

#### **Performance - Lifting forces**

F75	Vertical (N)	Parallel (N)
20 -kPa	80	60
60 -kPa	200	110
90 -kPa	270	140

vı.	9	+ 4	٦r	ia	


Name Colour

Temperature, min.   °C	-30
Temperature max.   °C	140
Hardness   °Shore A	75
Material resistance	
Alcohol	Good
Concentrated acids	Fair
Ethanol	n/a
Hydrolysis	Good
Methanol	n/a
Oil	Excellent
Oxidation	Excellent
Petrol	Excellent
Wear resistance	Excellent
Weather and ozone	Excellent

HNBR 75° Shore A

Blue/grey

#### **Dimensional drawings**



## Values specified in this data sheet are tested at (unless otherwise stated):

- •Room temperature (20°C [68°F]  $\pm$  3°C [5.5°F]).
- •Standard atmosphere (101.3 [29.9 inHg]  $\pm$  1.0 kPa [0.3 inHg]).
- •Relative humidity 20-70%.
- •Compressed air quality, DIN ISO 8573-1 class 4.

#### **Accessories**

0100548 | Fitting 75, 1/8" NPSF female, with mesh filter

0100551 | Fitting 75, G3/8" female, with mesh filter

0100552 | Fitting 75, G3/8" female, with cone valve

0100553 | Fitting 75, 3/8" NPSF female, with mesh filter

0100555 | Fitting 75, G1/2" female, with mesh filter

0100556 | Fitting 75, G1/2" female, with cone valve

0127819 | Fitting 1/8" NPSF female Al, with mesh filter

0127820 | Fitting G1/2" female Al, with mesh filter

3150131P | Suction cup F75 Nitrile-PVC

3150131S | Suction cup F75 Silicone

#### **Spare parts**

0127821 | Fitting 1/4" NPT female Al, with mesh filter & 10-32 addl. conn. 3150131T | Suction cup F75 HNBR

