Datasheet

Suction cup B40MF Thermoelastic polyurethane, G1/4" male, with mesh filter

Article number: 0101483



- Suction cup of TPU, a mark free material that leaves no trace on the object being handled.
- Suitable for level adjustment.
- Lifting movement to separate small and thin objects.
- Only lightweight objects should be handled when the lifting force is parallel to the surface.

Technical data

Description Uni		/alue
0 11 1	D	
Suction cup shape -	Б	Bellows
Application -	M	1ark Free
Suction cup design -	R	Round
Characteristics -	M	1ark free
Material -	T	PE
Weight, min. g	10	0
Suction cup model -	В	3-MF
Volume cm ³	3 15	5
Height mm	n 4.	13
Outer diameter, min. mm	n 4.	3.7
Outer diameter, actuated mm	n 41	17.5
Fitting size -	1,	/4"
Fitting option -	F	ilter mesh
Fitting style -	M	1ale
Fitting type -	G	G-thread
Suction cup model -	В	340MF
Movement, vertical max. mm	n 12	2.5
Curve radius, min. mm	n 22	2

Performance - Lifting forces

B40MF	Vertical (N)	Parallel (N)
20 -kPa	18	13.6
60 -kPa	57	40
90 -kPa	72	47

Material

Platerial	
Name	Thermoplastic Polyurethane (TPE-U)
Colour	White transparent
Temperature, min. °C	-20
Temperature max. °C	80
Hardness °Shore A	81
Material resistance	
Alcohol	Good
Concentrated acids	Poor
Ethanol	n/a
Hydrolysis	Poor
Methanol	n/a
Oil	Excellent
Oxidation	Good
Petrol	Poor
Wear resistance	Excellent
Weather and ozone	Excellent

Values specified in this data sheet are tested at (unless otherwise stated):

•Room temperature ($20^{\circ}C$ [$68^{\circ}F$] $\pm 3^{\circ}C$ [$5.5^{\circ}F$]).

•Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).

- •Relative humidity 20-70%.
- •Compressed air quality, DIN ISO 8573-1 class 4.

Accessories

0100261 | Fitting 5x1/8" NPSF female, 30–40 0101153 | Fitting 1/8" NPSF female, 30–40, with mesh filter 3250005 | Fitting 1/8" NPSF female, 30–40 3250086 | Fitting G3/8" male, 30–40, with mesh filter 3250089 | Fitting 3/8" NPT male, with mesh filter 3250093 | Fitting 1/4" NPT male, with mesh filter 3251006 | Fitting 1/4" NPSF female, 30–40, with dual flow control valve 3251007 | Fitting G1/4" male, 30–40, with mesh filter and dual flow control valve 3251008 | Fitting 1/4" NPT male, with dual flow control valve 3251008 | Fitting 1/4" NPT male, with dual flow control valve 3251009 | Fitting G3/8" male, 30–40, with mesh and dual flow control valve 3251010 | Fitting 3/8" NPT male, with dual flow control valve 3251011 | Fitting 5x1/8" NPSF female, 30–40, with dual flow control valve

Spare parts

0101113 | Suction cup B40MF Thermoelastic polyurethane 3250091 | Fitting G1/4" male, 30–40, with mesh filter