

Soft PVC hose in single layer, for ducting liquids.



 SMOOTH SURFACE *****


 FLEXIBILITY *****

 ABRASION RESISTENCE ***

 TEMPERATURE RANGE
-5 °c 60 °c

 CHEMICAL RESISTANCE
PVC Table

 CRUSHING RESISTANCE **

 FOR FOOD
EU according to Declaration of Conformity.

 O-PHTHALATE FREE *****

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	bending radius mm	total thickness mm	weight meter g/m	coil length m	Availability
3		3	6	24	1.5	25	200	In stock
4		4	6	32	1	19	200	In stock
4		4	7	32	1.5	32	200	In stock
4		4	8	30	2	49	200	On demand
5	3/16	5	8	40	1.5	35	200	In stock
5		5	8.3	40	1.7	45	200	On demand
6	1/4	6	9	48	1.5	44	200	In stock
7		7	10	56	1.5	50	100	In stock
8	5/16	8	12	64	2	85	100	In stock
9		9	13	72	2	85	100	On demand
10	3/8	10	14	80	2	90	100	In stock
12	1/2	12	16	120	2	110	100	On demand
12	1/2	12	17	120	2.5	140	100	In stock
13		13	19	130	3	190	100	In stock
14		14	19	140	2.5	160	100	In stock
15		15	20	150	2.5	170	100	On demand
16	5/8	16	21.5	160	3	215	100	In stock
18		18	23	175	2.5	200	50	On demand
18		18	25	180	3.5	290	50	In stock
19	3/4	19	25	160	3	275	50	On demand
20		20	25	195	2.5	220	50	On demand
20		20	27	200	3.5	320	50	In stock
22		22	30	220	4	380	50	In stock
25	1	25	31	245	3	350	50	On demand
25	1	25	34	250	4.5	530	50	In stock
30		30	40	300	5	680	30	In stock
35		35	45	350	5	760	30	In stock
40		40	50	400	5	900	30	In stock
50	2	50	60	500	5	1200	30	In stock