



TASKI® Jontec Lenio

Water-based wax maintainer

Description

Water-based wax. Suitable for unprotected and protected floors whether raw, oiled and varnished.

Key properties

- Cleans, maintains and protects
- Buffable, highly slip-resistant protective film
- Solvent-free
- Unique, patented Odour Neutralizing Technology (O.N.T.)

Benefits

- Protect floors against humidity in the grouts (especially raw and prevarnished parquets) and from premature wear
- Builds a safe to walk on and attractive silk-like protection
- Environmentally responsible and easy application (applicators/pads are easily rinsed with water)
- Leaves a pleasant, fresh fragrance
- Neutralises malodour molecules and therefore enhances the perfume effect

Use instructions

Full surface cleaning/maintenance:


1. For sealed wood, add the product into the spray device of a single disc machine, equipped with red pad, and spray clean the floor.
For unsealed wood apply one thin coat with a polish applicator.
2. Allow to dry, then immediately buff.
3. Unsealed wood floors may require a second coat (mat in between the 2 coats).
4. Allow to dry completely before applying additional coats.
5. After the floors has dried, buff the entire area with a white or red pad to densify the film.

Spray cleaning:

1. Add the product into the spray device of a single disc machine, equipped with an appropriate pad, and spray clean the floor.
2. After a short drying time, buff the whole surface for a more uniform appearance/ gloss level.
3. **Stripping:** Spray clean the surface with TASKI Jontec Solve and a single disc machine, equipped with a blue pad.

Spot cleaning/maintenance:

1. Add the product into the spray device of a single disc machine, equipped with an appropriate pad, and spray clean the floor by spraying only on spots/soiled areas.
2. After a short drying time, buff the whole surface for a more uniform appearance/ gloss level.



© A.I.S.E.

**This dosage is according to optimal conditions, recommendations may vary, please consult with your Diversey representative for directions.*



TASKI® Jontec Lenio

Dosage:

Initial treatment, protection application :

Ready to use, no dilution required.

Single disc machine (spray method): 375 ml/750 ml (50%).

Maintaining application :

Single disc machine (spray method): 23 ml/750 ml (3%).

Technical data

Appearance: Milky, white liquid

pH value (neat): ≈ 4

Relative density (20°C): 1.004 g/cm³

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet; sds.diversey.com. Store in original closed containers away from extremes of temperature.

Only for professional users / specialists. Do not store or use at temperatures below 5°C.

Product compatibility

Shake well before use. Depending on floor traffic, the first use of the product may require several spray and buffing/densifying cycles in the beginning; cycle intervals can later be extended.

Apply watery cleaning solutions very sparingly and always immediately pick up/wet vacuum.

Approvals

Slip resistance 0.5 minimum (ASTMD D 2047).

Available pack sizes

TASKI Jontec Lenio is available in 2x5L.