



TASKI® Jontec Plaza

Sealer/high gloss emulsion for stone floors 2 in 1

Description

Premium high gloss emulsion specially designed to coat stone, terrazzo, unglazed ceramic floors and marble. The product delivers excellent adhesion on most stone types, therefore no additional sealer is required. It can be applied as one-coat to fill the pores and ease cleaning or as multi-coat application for additional gloss and appearance.

Key properties

- Delivers a warm gloss, protective layer
- Traffic resistant
- Non-yellowing formula
- Excellent adhesion on stone floors
- Slip resistant according to international standards (ASTM D-2047)

Benefits


- Protects your floor investment against traffic abuses and eases cleaning
- Specially resistant against scuff and black heel marks
- Does not yellow under UV-light and delivers a uniform appearance
- Guarantees safety for your employees, patients and customers
- Can be used directly on the floor as pore filler, as sealer to apply additional coats of a different gloss floor emulsion or as multi-coat system for a high gloss, traffic resistant coating

Use instructions

1. Treat only stripped and thoroughly rinsed and completely dry floors.
2. Sparingly pour the product onto the floor and evenly spread it while still wet with a polish applicator in overlapping lanes of 1-1.5m.
3. Apply one coat on porous floors to ease cleaning while maintaining the properties of the floor.
4. Apply 2-3 coats to get a warm, high gloss floor finish which can be maintained with standard maintenance methods (scrubber-drying, spray cleaning etc.) or 1-2 coats as sealer to apply a different top coat (e.g. matt or silk like appearance).
5. After the last coat, allow minimum 60 minutes before traffic.

Dosage:

Ready to use, no dilution required.



© A.I.S.E.



TASKI® Jontec Plaza

Technical data

Appearance: Milky, white liquid

pH value (neat): ≈ 9

pH value (in use): ≈ 9

Relative density (20°C): 1.03 g/cm³

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet; sds.diversey.com. Store in original closed containers away from extremes of temperature.

Only for professional users / specialists. Do not store or use at temperatures below 5°C.

Product compatibility

Treat only deep cleaned, thoroughly rinsed and completely dry floors. Do not dilute or mix with other substances. Do not use outdoors or in wet zones. Do not use on glazed ceramic floors.

Approvals

Tested according to ASTM D-2047 for slip resistance.

Available pack sizes

TASKI Jontec Plaza is available in 2x5L.