SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product identifier.	5FMW7
Product name.	70% WHITE A/C FM BASE (ZIP036)
UFI	No Information

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use.	Industrial Wood Coating
Uses advised against.	Professional Use Only

1.3. Details of the supplier of the safety data sheet

Supplier.	Morrells Woodfinishes Ltd Wellington Works Mill Lane, Woodley Stockport SK6 1RN Tel: +44 (0)161 406 5300 Fax: +44 (0)161 406 6276 EMail: enquires@morrells.co.uk
1.4. Emergency telephone number	Chemtrec: +1-800-424-9300 USA Chemtrec: +1 703-527-3887 ex-USA 24 hrs./day, 7 days/week
Europe	112
Austria	+43 1 406 43 43
Belgium	Poison center (BE): +32 70 245 245
Denmark	Poison Control Hotline (DK): +45 82 12 12 12
Finland	Poison Information Centre (FI):+358 9 471 977
France	ORFILA (FR): + 01 45 42 59 59
Germany	Poison Center Berlin (DE): +49 030 30686 790 |par Poison Center Nord: +49 551 19240 (24h available English / German)
Ireland	National Poisons Information Centre (IE): +353 1 8379964 / + 353 1 8092566
Iceland	+354 543 2222
Italy	Poison Center, Milan (IT): +39 02 6610 1029
Luxembourg	112
Netherlands	National Poisons Information Center (NL): +31 88 755 8000 (NB: this service is only available to health professionals)
Norway	Poisons Information (NO):+ 47 22 591300
Portugal	Poison Information Center (PT): +351 21 330 3284
Spain	Poison Information Service (ES): +34 91 562 04 20
Sweden	Poisons Information Center (SV):+46 8 33 12 31
Switzerland	Poison Center: Tel 145; +41 44 251 51 51
United Kingdom	111 / 0300 020 0155

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flammable Liquid, category 2
Germ Cell Mutagenicity, category 1B
Carcinogenicity, category 1B
Reproductive_ToxicityD_category_2
Skin Irritation, category 2
Serious Eye Damage, category 1
Skin Sensitizer, category 1
Hazardous to the aquatic environment, Chronic, category 3

2.2. Label elements

Signal Word
Danger

Hazardous ingredients which must be listed on the label
Not Applicable

Possible Hazards
8.5% of the mixture consists of ingredient(s) of unknown toxicity
8.5% of the mixture consists of ingredient(s) of unknown acute inhalation toxicity

GHS HAZARD STATEMENTS

H350	May cause cancer.
H225	Highly flammable liquid and vapour.
H340	May cause genetic defects.
H412	Harmful to aquatic life with long lasting effects.
H361D	Suspected of damaging the unborn child.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

GHS SDS PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash contaminated skin thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER or doctor/physician.
P321	Specific treatment (see supplemental first aid instructions on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use carbon dioxide to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with national regulations.

2.3. Other hazards

EMERGENCY OVERVIEW: No Information

SECTION 3: Composition/information on ingredients

3.1. Substances

This product is a mixture. Health hazard information is based on its components.

3.2. Mixtures

Chemical Name	CAS-No.	EC No.	REACH Reg No.	Wt. %
Xylene	1330-20-7	215-535-7	No Information	>=10 - <20
Titanium dioxide	13463-67-7	236-675-5	No Information	>=10 - <20
ISOBUTYL ALCOHOL	78-83-1	201-148-0	No Information	>=5 - <10
Ethanol	64-17-5	200-578-6	No Information	>=3 - <7

Toluene	108-88-3	203-625-9	No Information	>=1 - <5
2-Methoxy-1-methylethyl acetate	108-65-6	203-603-9	No Information	>=1 - <3
2-(2-BUTOXYETHOXY)ETHANOL	112-34-5	203-961-6	No Information	<1
Solvent naphtha (petroleum), light aromatic	64742-95-6	265-199-0	No Information	<0.3
METHANOL	67-56-1	200-659-6	No Information	<1
2,6-Dimethylheptan-4-one	108-83-8	203-620-1	No Information	<1
Formaldehyde	50-00-0	200-001-8	No Information	<0.1
Maleic Anhydride	108-31-6	203-571-6	No Information	<0.1

Chemical Name	**Classification (1272/2008/EC)**	**Specific Conc. Limits, M-factors and ATEs**
Xylene	Flam. Liq. 3 (H226) Skin Irrit. 2 (H315) Acute Tox. 4 Inhalation (H332)	ATE oral (mg/kg): 3500 mg/kg Rat ATE dermal (mg/kg): >4350 mg/kg Rabbit ATE inhalation - vapor (mg/l/4h): N.R. ATE inhalation - dust/mist (mg/l/4h): N.R.
Titanium dioxide	Not classified	ATE oral (mg/kg): N.R. ATE dermal (mg/kg): N.R. ATE inhalation - vapor (mg/l/4h): N.R. ATE inhalation - dust/mist (mg/l/4h): N.R.
ISOBUTYL ALCOHOL	Flam. Liq. 3 (H226) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Acute Tox. 4 Inhalation (H332) STOT SE 3 RTI (H335) STOT SE 3 NE (H336)	ATE oral (mg/kg): 2460 mg/kg Rat ATE dermal (mg/kg): 3400 mg/kg Rabbit ATE inhalation - vapor (mg/l/4h): >18.18 mg/L Rat
Ethanol	Flam. Liq. 2 (H225) Aquatic Chronic 2 (H411)	ATE oral (mg/kg): 7060 mg/kg Rat ATE dermal (mg/kg): N.R. ATE inhalation - vapor (mg/l/4h): 116.9 mg/L, 133.8 mg/L Rat ATE inhalation - dust/mist (mg/l/4h): N.R.
Toluene	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 NE (H336) Repr. 2 (H361D) STOT RE 2 (H373)	ATE oral (mg/kg): 2600 mg/kg Rat ATE dermal (mg/kg): 12000 mg/kg Rabbit ATE inhalation - vapor (mg/l/4h): N.R. ATE inhalation - dust/mist (mg/l/4h): N.R.
2-Methoxy-1-methylethyl acetate	Flam. Liq. 3 (H226)	ATE oral (mg/kg): N.R. ATE dermal (mg/kg): N.R. ATE inhalation - vapor (mg/l/4h): N.R. ATE inhalation - dust/mist (mg/l/4h): N.R.
2-(2-BUTOXYETHOXY)ETHANOL	Eye Irrit. 2 (H319)	ATE oral (mg/kg): 5660 mg/kg Rat ATE dermal (mg/kg): 2700 mg/kg Rabbit ATE inhalation - vapor (mg/l/4h): N.R. ATE inhalation - dust/mist (mg/l/4h): N.R.
Solvent naphtha (petroleum), light aromatic	Asp. Tox. 1 (H304) Muta. 1B (H340) Carc. 1B (H350)	ATE oral (mg/kg): 8400 ATE dermal (mg/kg): N.R. ATE inhalation - vapor (mg/l/4h): N.R. ATE inhalation - dust/mist (mg/l/4h): N.R.
METHANOL	Flam. Liq. 2 (H225) STOT SE 1 (H370) Aquatic Chronic 3 (H412)	ATE oral (mg/kg): 6200 mg/kg Rat ATE dermal (mg/kg): 15840 mg/kg Rabbit ATE inhalation - vapor (mg/l/4h): N.R. ATE inhalation - dust/mist (mg/l/4h): N.R.
2,6-Dimethylheptan-4-one	Flam. Liq. 3 (H226) Acute Tox. 3 Inhalation (H331) STOT SE 3 RTI (H335)	ATE oral (mg/kg): 5750 mg/kg Rat ATE dermal (mg/kg): 2002 ATE inhalation - vapor (mg/l/4h): N.R. ATE inhalation - dust/mist (mg/l/4h): N.R.
Formaldehyde	Acute Tox. 3 Oral (H301) Skin Corr. 1B (H314) Skin Sens. 1 (H317) Acute Tox. 3 Inhalation (H331) STOT SE 3 RTI (H335) Muta. 2 (H341) Carc. 1B (H350)	ATE oral (mg/kg): 100 mg/kg Rat ATE dermal (mg/kg): >2000 mg/kg Rat

Maleic Anhydride	EUH071 Acute Tox. 3 Oral (H301) Skin Corr. 1B (H314) Skin Sens. 1A (H317) Acute Tox. 2 Inhalation (H330) Resp. Sens. 1 (H334) STOT RE 1 (H372)	ATE oral (mg/kg): 235 mg/kg Rat ATE dermal (mg/kg): 2620 mg/kg Rabbit ATE inhalation - dust/mist (mg/l/4h): 0.16 mg/L Rat

For the full text of the H-Statements mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice.

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. Do not get in eyes, on skin, or on clothing. May cause allergic skin reaction. Do not delay care and transport of a seriously injured person. Remove and isolate contaminated clothing and shoes. Use first aid treatment according to the nature of the injury. Move out of dangerous area. Use personal protective equipment. Remove all sources of ignition. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin. See section 8 for more information. Ensure adequate ventilation.

Inhalation.

Remove from exposure, lie down. Remove person to fresh air. If signs/symptoms continue, get medical attention. Remove to fresh air. Keep victim warm and quiet. If unconscious place in recovery position and seek medical advice. Artificial respiration and/or oxygen may be necessary. Administer oxygen if breathing is difficult. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a doctor immediately if allergic signs, particularly in the respiratory tract, are observed. Get medical attention if symptoms occur.

Skin contact.

Take off contaminated clothing and shoes immediately. Allergic symptoms may develop within 12 hours after exposure. In the case of skin irritation or allergic reactions see a physician. Wash off immediately with soap and plenty of water for at least 15 minutes. Do not remove clothing if adhering to skin. Wash contaminated clothing before reuse. Thoroughly clean shoes before reuse.

Eye contact.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. May produce an allergic reaction. Do not rub affected area. Get medical attention immediately.

Ingestion.

Rinse mouth. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. Remove from exposure, lie down. If swallowed, call a poison control center or doctor immediately. Keep at rest. Allergic symptoms may develop within 12 hours after exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms.

Hives. Itching. Burning. Rashes. May cause allergic skin reaction. Skin irritation. Eye irritation. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician.

Treat symptomatically. May cause sensitization of susceptible persons. Effects of contact or inhalation may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media.

Use:. Dry chemical. Carbon dioxide (CO_2). Water spray or fog. Alcohol-resistant foam. Move containers from fire area if you can do it without risk.

Extinguishing media which shall not be used for safety reasons.

Do not use a solid water stream as it may scatter and spread fire. Water may be ineffective.

5.2. Special hazards arising from the substance or mixture

The product causes burns of eyes, skin and mucous membranes. Flammable. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Runoff may pollute waterways. Vapor explosion hazard indoors, outdoors or in sewers. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Will be easily ignited by heat, sparks or flames. Product is or contains a sensitizer. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Do not allow run-off from fire fighting to enter drains or water courses. Cool drums with water spray. Fire will produce dense black smoke containing hazardous combustion products (see section 10). Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Container may explode in heat of fire.

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.Keep away from sources of ignition. Prevent fire fighting water from entering surface water or groundwater. Cool containers with spray water from a safe distance. Never use welding or cutting torch on or near container (even empty) because product may ignite explosively.Cool closed containers exposed to fire with water spray.
Pay attention to flashback. Refer to protective measures listed in sections 7 and 8.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions.

Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. Pay attention to flashback. All equipment used when handling the product must be grounded. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stop leak if you can do it without risk. Do not get in eyes, on skin, or on clothing. A vapor suppressing foam may be used to reduce vapors. Wash thoroughly after handling. Contaminated surfaces will be extremely slippery. Refer to protective measures listed in sections 7 and 8. Do not breathe dust. Corrosive.

Advice for emergency responders.

Pay attention to flashback. Refer to protective measures listed in sections 7 and 8.

6.2. Environmental precautions

Should not be released into the environment. Prevent entry into waterways, sewers, basements or confined areas. Prevent spreading of vapors through sewers, ventilation systems and confined areas. Dispose of contents/container to an approved waste disposal plant. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

6.3. Methods and material for containment and cleaning up

Methods for Containment.

No Information

Methods for cleaning up.

No Information

Other information.

All equipment used when handling the product must be grounded. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate the area. Use personal protective equipment as required.

6.4. Reference to other sections

See Section 8, 13 for additional information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling.

Use spark-proof tools and explosion-proof equipment. Wear personal protective equipment. Remove and wash contaminated clothing before re-use. Take precautionary measures against static discharges. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation at machinery. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Wash thoroughly after handling. Never pierce, drill, grind, cut, saw or weld any empty container. Provide sufficient air exchange and/or exhaust in work rooms. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Keep product and empty container away from heat and sources of ignition. Electrical equipment should be protected to the appropriate standard. Keep container closed when not in use. Ground and bond containers when transferring material.

Hygiene measures.

Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Handle in accordance with good industrial hygiene and safety practice. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin, eyes and clothing. Wash hands before breaks and at the end of workday. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions.

Keep in a bunded area. Keep in properly labeled containers. Keep container tightly closed. Keep in an area equipped with sprinklers. Keep out of the reach of children. Store in accordance with the particular national regulations. Store in accordance with local regulations. Ensure all equipment is electrically grounded before beginning transfer operations. Use spark-proof tools and explosion-proof equipment. Keep locked up or in an area accessible only to qualified or authorized persons. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Store between 41 and 77 °F (5 - 25° C) in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.3. Specific end use(s)

Specific use(s).

No Information

Exposure scenario.

No Information Available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limit Values

Chemical Name	Austria	Belgium	Denmark	European Union.	Finland	France
Xylene 1330-20-7	STEL: 100 ppm STEL: 442 mg/m3 TWA: 50 ppm TWA: 221 mg/m3	STEL: 100 ppm STEL: 442 mg/m3 TWA: 50 ppm TWA: 221 mg/m3	TWA: 25 ppm TWA: 109 mg/m3	STEL: 100 ppm STEL: 442 mg/m3 TWA: 50 ppm TWA: 221 mg/m3	STEL: 100 ppm STEL: 440 mg/m3 TWA: 50 ppm TWA: 220 mg/m3	STEL: 100 ppm STEL: 442 mg/m3 TWA: 50 ppm TWA: 221 mg/m3
Titanium dioxide 13463-67-7	STEL: 10 mg/m3 TWA: 5 mg/m3	TWA: 10 mg/m3	TWA: 6 mg/m3	N.D.	N.D.	TWA: 10 mg/m3
ISOBUTYL ALCOHOL 78-83-1	STEL: 200 ppm STEL: 600 mg/m3 TWA: 50 ppm TWA: 150 mg/m3	TWA: 50 ppm TWA: 154 mg/m3	N.D.	N.D.	STEL: 75 ppm STEL: 230 mg/m3 TWA: 150 mg/m3 TWA: 50 ppm	TWA: 50 ppm TWA: 150 mg/m3
Ethanol 64-17-5	STEL: 2000 ppm STEL: 3800 mg/m3 TWA: 1000 ppm TWA: 1900 mg/m3	TWA: 1000 ppm TWA: 1907 mg/m3	TWA: 1000 ppm TWA: 1900 mg/m3	N.D.	STEL: 1300 ppm STEL: 2500 mg/m3 TWA: 1000 ppm TWA: 1900 mg/m3	STEL: 5000 ppm STEL: 9500 mg/m3 TWA: 1000 ppm TWA: 1900 mg/m3
Toluene 108-88-3	STEL: 100 ppm STEL: 380 mg/m3 TWA: 50 ppm TWA: 190 mg/m3	STEL: 100 ppm STEL: 384 mg/m3 TWA: 20 ppm TWA: 77 mg/m3	TWA: 25 ppm TWA: 94 mg/m3	STEL: 100 ppm STEL: 384 mg/m3 TWA: 50 ppm TWA: 192 mg/m3	STEL: 100 ppm STEL: 380 mg/m3 TWA: 25 ppm TWA: 81 mg/m3	STEL: 100 ppm STEL: 384 mg/m3 TWA: 20 ppm TWA: 76.8 mg/m3
2-Methoxy-1-methylethyl acetate 108-65-6	STEL: 100 ppm STEL: 550 mg/m3 TWA: 50 ppm TWA: 275 mg/m3	STEL: 100 ppm STEL: 550 mg/m3 TWA: 50 ppm TWA: 275 mg/m3	TWA: 50 ppm TWA: 275 mg/m3	STEL: 100 ppm STEL: 550 mg/m3 TWA: 50 ppm TWA: 275 mg/m3	STEL: 100 ppm STEL: 550 mg/m3 TWA: 50 ppm TWA: 270 mg/m3	STEL: 100 ppm STEL: 550 mg/m3 TWA: 50 ppm TWA: 275 mg/m3
2-(2-BUTOXYETHOXY)ETHANOL 112-34-5	STEL: 15 ppm STEL: 101.2 mg/m3 TWA: 10 ppm TWA: 67.5 mg/m3	STEL: 15 ppm STEL: 101.2 mg/m3 TWA: 10 ppm TWA: 67.5 mg/m3	TWA: 10 ppm TWA: 68 mg/m3	STEL: 15 ppm STEL: 101.2 mg/m3 TWA: 10 ppm TWA: 67.5 mg/m3	TWA: 10 ppm TWA: 68 mg/m3	STEL: 15 ppm STEL: 101.2 mg/m3 TWA: 10 ppm TWA: 68 mg/m3
Solvent naphtha (petroleum), light aromatic 64742-95-6	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.

Chemical Name	Austria	Belgium	Denmark	European Union.	Finland	France
METHANOL 67-56-1	STEL: 800 ppm STEL: 1040 mg/m3 TWA: 200 ppm TWA: 260 mg/m3	STEL: 250 ppm STEL: 333 mg/m3 TWA: 200 ppm TWA: 266 mg/m3	TWA: 200 ppm TWA: 260 mg/m3	TWA: 200 ppm TWA: 260 mg/m3	STEL: 250 ppm STEL: 330 mg/m3 TWA: 200 ppm TWA: 270 mg/m3	STEL: 1000 ppm STEL: 1300 mg/m3 TWA: 200 ppm TWA: 260 mg/m3
2,6-Dimethylheptan-4-one 108-83-8	TWA: 50 ppm TWA: 290 mg/m3	TWA: 25 ppm TWA: 147 mg/m3	TWA: 25 ppm TWA: 150 mg/m3	N.D.	STEL: 40 ppm STEL: 240 mg/m3 TWA: 25 ppm TWA: 150 mg/m3	TWA: 25 ppm TWA: 250 mg/m3
Formaldehyde 50-00-0	STEL: 0.6 ppm STEL: 0.74 mg/m3 TWA: 0.3 ppm TWA: 0.37 mg/m3	STEL: 0.3 ppm STEL: 0.38 mg/m3	TWA: 0.3 ppm TWA: 0.37 mg/m3	N.D.	STEL: 0.6 ppm STEL: 0.74 mg/m3 TWA: 0.3 ppm TWA: 0.37 mg/m3	STEL: 0.6 ppm STEL: 0.74 mg/m3 TWA: 0.5 ppm TWA: 0.3 ppm TWA: 0.37 mg/m3 TWA: 0.62 mg/m3
Maleic Anhydride 108-31-6	STEL: 0.2 ppm STEL: 0.8 mg/m3 TWA: 0.1 ppm TWA: 0.4 mg/m3	TWA: 0.0025 ppm TWA: 0.01 mg/m3	TWA: 0.1 ppm TWA: 0.4 mg/m3	N.D.	TWA: 0.1 ppm TWA: 0.41 mg/m3	STEL: 1 mg/m3

Chemical Name	Germany	Iceland	Ireland	Italy	Luxembourg	Netherlands
Xylene 1330-20-7	STEL: 100 ppm STEL: 440 mg/m3 TWA: 50 ppm TWA: 220 mg/m3	STEL: 100 ppm STEL: 442 mg/m3 TWA: 25 ppm TWA: 109 mg/m3	STEL: 100 ppm STEL: 442 mg/m3 TWA: 50 ppm TWA: 221 mg/m3	STEL: 100 ppm STEL: 442 mg/m3 TWA: 50 ppm TWA: 221 mg/m3	STEL: 100 ppm STEL: 442 mg/m3 TWA: 50 ppm TWA: 221 mg/m3	STEL: 442 mg/m3 TWA: 210 mg/m3
Titanium dioxide 13463-67-7	STEL: 2.4 mg/m3 TWA: 0.3 mg/m3	TWA: 6 mg/m3	STEL: 30 mg/m3 STEL: 12 mg/m3 TWA: 10 mg/m3 TWA: 4 mg/m3	N.D.	N.D.	N.D.
ISOBUTYL ALCOHOL 78-83-1	STEL: 100 ppm STEL: 310 mg/m3 TWA: 100 ppm TWA: 310 mg/m3	STEL: 50 ppm STEL: 150 mg/m3	STEL: 225 mg/m3 STEL: 75 ppm TWA: 150 mg/m3 TWA: 50 ppm	N.D.	N.D.	N.D.
Ethanol 64-17-5	STEL: 800 ppm STEL: 1520 mg/m3 TWA: 200 ppm TWA: 380 mg/m3	TWA: 1000 ppm TWA: 1900 mg/m3	STEL: 1000 ppm	N.D.	N.D.	STEL: 1900 mg/m3 TWA: 260 mg/m3
Toluene 108-88-3	STEL: 100 ppm STEL: 380 mg/m3 TWA: 50 ppm TWA: 190 mg/m3	STEL: 50 ppm STEL: 188 mg/m3 TWA: 25 ppm TWA: 94 mg/m3	STEL: 384 mg/m3 STEL: 100 ppm TWA: 192 mg/m3 TWA: 50 ppm	TWA: 50 ppm TWA: 192 mg/m3	STEL: 100 ppm STEL: 384 mg/m3 TWA: 50 ppm TWA: 192 mg/m3	STEL: 384 mg/m3 TWA: 150 mg/m3
2-Methoxy-1-methylethyl acetate 108-65-6	STEL: 50 ppm STEL: 270 mg/m3 TWA: 50 ppm TWA: 270 mg/m3	STEL: 100 ppm STEL: 550 mg/m3 TWA: 50 ppm TWA: 275 mg/m3	STEL: 100 ppm STEL: 550 mg/m3 TWA: 50 ppm TWA: 275 mg/m3	STEL: 100 ppm STEL: 550 mg/m3 TWA: 50 ppm TWA: 275 mg/m3	STEL: 100 ppm STEL: 550 mg/m3 TWA: 50 ppm TWA: 275 mg/m3	TWA: 550 mg/m3
2-(2-BUTOXYETHOXY)ETHANOL 112-34-5	STEL: 15 ppm STEL: 100.5 mg/m3 TWA: 67 mg/m3 TWA: 10 ppm	STEL: 15 ppm STEL: 101.2 mg/m3 TWA: 10 ppm TWA: 67.5 mg/m3	STEL: 15 ppm STEL: 101.2 mg/m3 TWA: 10 ppm TWA: 67.5 mg/m3	STEL: 15 ppm STEL: 101.2 mg/m3 TWA: 10 ppm TWA: 67.5 mg/m3	STEL: 15 ppm STEL: 101.2 mg/m3 TWA: 10 ppm TWA: 67.5 mg/m3	STEL: 100 mg/m3 TWA: 50 mg/m3
Solvent naphtha (petroleum), light aromatic 64742-95-6	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
METHANOL 67-56-1	STEL: 200 ppm STEL: 260 mg/m3 TWA: 100 ppm TWA: 130 mg/m3	TWA: 200 ppm TWA: 260 mg/m3	STEL: 600 ppm STEL: 780 mg/m3 TWA: 200 ppm TWA: 260 mg/m3	TWA: 200 ppm TWA: 260 mg/m3	TWA: 200 ppm TWA: 260 mg/m3	TWA: 133 mg/m3

Chemical Name	Germany	Iceland	Ireland	Italy	Luxembourg	Netherlands
2,6-Dimethylheptan-4-one 108-83-8	N.D.	TWA: 25 ppm TWA: 150 mg/m3	STEL: 75 ppm STEL: 450 mg/m3 TWA: 25 ppm TWA: 150 mg/m3	N.D.	N.D.	N.D.
Formaldehyde 50-00-0	STEL: 0.6 ppm STEL: 0.74 mg/m3 TWA: 0.3 ppm TWA: 0.37 mg/m3	STEL: 0.6 ppm STEL: 0.74 mg/m3 TWA: 0.3 ppm TWA: 0.37 mg/m3	STEL: 0.6 ppm STEL: 0.738 mg/m3 STEL: 0.62 mg/m3 TWA: 0.3 ppm TWA: 0.5 ppm TWA: 0.37 mg/m3 TWA: 0.62 mg/m3	STEL: 0.74 mg/m3 STEL: 0.6 mg/m3 TWA: 0.37 mg/m3 TWA: 0.3 ppm TWA: 0.62 mg/m3 TWA: 0.5 ppm	N.D.	STEL: 0.5 mg/m3 TWA: 0.15 mg/m3
Maleic Anhydride 108-31-6	STEL: 0.02 ppm STEL: 0.081 mg/m3 TWA: 0.02 ppm TWA: 0.081 mg/m3	TWA: 0.1 ppm TWA: 0.4 mg/m3	STEL: 0.03 ppm TWA: 0.01 ppm	N.D.	N.D.	N.D.

Chemical Name	Norway	Portugal	Spain	Sweden	Switzerland	United Kingdom
Xylene 1330-20-7	STEL: 37.5 ppm STEL: 135 mg/m3 TWA: 25 ppm TWA: 108 mg/m3	STEL: 100 ppm STEL: 442 mg/m3 TWA: 50 ppm TWA: 221 mg/m3	STEL: 100 ppm STEL: 442 mg/m3 TWA: 50 ppm TWA: 221 mg/m3	STEL: 100 ppm STEL: 442 mg/m3 TWA: 50 ppm TWA: 221 mg/m3	STEL: 100 ppm STEL: 440 mg/m3 TWA: 50 ppm TWA: 220 mg/m3	STEL: 100 ppm STEL: 441 mg/m3 TWA: 50 ppm TWA: 220 mg/m3
Titanium dioxide 13463-67-7	STEL: 10 mg/m3 TWA: 5 mg/m3	TWA: 10 mg/m3	TWA: 10 mg/m3	TWA: 5 mg/m3	TWA: 3 mg/m3 TWA: 3 mg/m3 TWA: 10 mg/m3	STEL: 30 mg/m3 STEL: 12 mg/m3 TWA: 10 mg/m3 TWA: 4 mg/m3
ISOBUTYL ALCOHOL 78-83-1	N.D.	TWA: 50 ppm	TWA: 50 ppm TWA: 154 mg/m3	STEL: 75 ppm STEL: 250 mg/m3 TWA: 50 ppm TWA: 150 mg/m3	STEL: 50 ppm STEL: 150 mg/m3 TWA: 50 ppm TWA: 150 mg/m3	STEL: 75 ppm STEL: 231 mg/m3 TWA: 50 ppm TWA: 154 mg/m3
Ethanol 64-17-5	STEL: 625 ppm STEL: 1187.5 mg/m3 TWA: 500 ppm TWA: 950 mg/m3	STEL: 1000 ppm	STEL: 1000 ppm STEL: 1910 mg/m3	STEL: 1000 ppm STEL: 1900 mg/m3 TWA: 500 ppm TWA: 1000 mg/m3	STEL: 1000 ppm STEL: 1920 mg/m3 TWA: 500 ppm TWA: 960 mg/m3	STEL: 3000 ppm STEL: 5760 mg/m3 TWA: 1000 ppm TWA: 1920 mg/m3
Toluene 108-88-3	STEL: 37.5 ppm STEL: 141 mg/m3 TWA: 25 ppm TWA: 94 mg/m3	STEL: 100 ppm STEL: 384 mg/m3 TWA: 50 ppm TWA: 192 mg/m3	STEL: 100 ppm STEL: 384 mg/m3 TWA: 50 ppm TWA: 192 mg/m3	STEL: 100 ppm STEL: 384 mg/m3 TWA: 50 ppm TWA: 192 mg/m3	STEL: 200 ppm STEL: 760 mg/m3 TWA: 50 ppm TWA: 190 mg/m3	STEL: 100 ppm STEL: 384 mg/m3 TWA: 50 ppm TWA: 191 mg/m3
2-Methoxy-1-methylethyl acetate 108-65-6	STEL: 75 ppm STEL: 337.5 mg/m3 TWA: 50 ppm TWA: 270 mg/m3	STEL: 100 ppm STEL: 550 mg/m3 TWA: 50 ppm TWA: 275 mg/m3	STEL: 100 ppm STEL: 550 mg/m3 TWA: 50 ppm TWA: 275 mg/m3	STEL: 100 ppm STEL: 550 mg/m3 TWA: 50 ppm TWA: 275 mg/m3	STEL: 50 ppm STEL: 275 mg/m3 TWA: 50 ppm TWA: 275 mg/m3	STEL: 100 ppm STEL: 548 mg/m3 TWA: 50 ppm TWA: 274 mg/m3
2-(2-BUTOXYETHOXY)ETHANOL 112-34-5	STEL: 20 ppm STEL: 102 mg/m3 TWA: 10 ppm TWA: 68 mg/m3	STEL: 101.2 mg/m3 STEL: 15 ppm TWA: 10 ppm TWA: 67.5 mg/m3	STEL: 15 ppm STEL: 101.2 mg/m3 TWA: 10 ppm TWA: 67.5 mg/m3	STEL: 15 ppm STEL: 101 mg/m3 TWA: 10 ppm TWA: 68 mg/m3	STEL: 15 ppm STEL: 101 mg/m3 TWA: 10 ppm TWA: 67 mg/m3	STEL: 15 ppm STEL: 101.2 mg/m3 TWA: 10 ppm TWA: 67.5 mg/m3
Solvent naphtha (petroleum), light aromatic 64742-95-6	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
METHANOL 67-56-1	STEL: 150 ppm STEL: 162.5 mg/m3 TWA: 100 ppm TWA: 130 mg/m3	STEL: 250 ppm TWA: 200 ppm TWA: 260 mg/m3	TWA: 200 ppm TWA: 266 mg/m3	STEL: 250 ppm STEL: 350 mg/m3 TWA: 200 ppm TWA: 250 mg/m3	STEL: 400 ppm STEL: 520 mg/m3 TWA: 200 ppm TWA: 260 mg/m3	STEL: 250 ppm STEL: 333 mg/m3 TWA: 200 ppm TWA: 266 mg/m3
2,6-Dimethylheptan-4-one 108-83-8	STEL: 30 ppm STEL: 150 mg/m3 TWA: 20 ppm TWA: 120 mg/m3	TWA: 25 ppm	TWA: 25 ppm TWA: 148 mg/m3	N.D.	TWA: 25 ppm TWA: 150 mg/m3	STEL: 75 ppm STEL: 444 mg/m3 TWA: 25 ppm TWA: 148 mg/m3

Chemical Name	Norway	Portugal	Spain	Sweden	Switzerland	United Kingdom
Formaldehyde 50-00-0	STEL: 0.74 mg/m3 STEL: 0.6 ppm TWA: 0.37 mg/m3 TWA: 0.3 ppm	STEL: 0.6 ppm STEL: 0.74 mg/m3 TWA: 0.3 ppm TWA: 0.37 mg/m3 TWA: 0.62 mg/m3 TWA: 0.5 ppm	STEL: 0.6 ppm STEL: 0.74 mg/m3 TWA: 0.3 ppm TWA: 0.37 mg/m3	STEL: 0.6 ppm STEL: 0.74 mg/m3 TWA: 0.3 ppm TWA: 0.37 mg/m3	STEL: 0.6 ppm STEL: 0.74 mg/m3 TWA: 0.3 ppm TWA: 0.37 mg/m3	STEL: 2 ppm STEL: 2.5 mg/m3 TWA: 2 ppm TWA: 2.5 mg/m3
Maleic Anhydride 108-31-6	STEL: 0.6 ppm STEL: 2.4 mg/m3 TWA: 0.2 ppm TWA: 0.8 mg/m3	TWA: 0.01 mg/m3	TWA: 0.1 ppm TWA: 0.4 mg/m3	STEL: 0.1 ppm STEL: 0.4 mg/m3 TWA: 0.05 ppm TWA: 0.2 mg/m3	STEL: 0.1 ppm STEL: 0.4 mg/m3 TWA: 0.1 ppm TWA: 0.4 mg/m3	STEL: 3 mg/m3 TWA: 1 mg/m3

TWA: Time weighted average
STEL: Short term exposure limit.

Derived No Effect Level (DNEL)

No Information Available

Predicted No Effect Concentration (PNEC)

No Information Available

8.2. Exposure controls

Engineering Measures.

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protective equipment.

Eye/Face Protection.

Tightly fitting safety goggles. If splashes are likely to occur, wear:. Face-shield. Chemical resistant goggles must be worn.

Skin and body protection.

No special protective equipment required. Solvent-resistant gloves. Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Follow the skin protection plan. Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Flame retardant antistatic protective clothing. Antistatic boots.

The selected protective gloves have to satisfy the specifications of EU Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Respiratory protection.

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. In the case of dust or aerosol formation use respirator with an approved filter. Preferably a compressed airline breathing apparatus. Breathing apparatus with filter. Respirator with filter for organic vapor. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Environmental Exposure Controls.

Prevent product from entering drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	No Information
Colour	White
Odour	No Information
Odour Threshold	No Information
pH	No Information
Melting Point, °C	No Information
Flash Point, °C	4
Boiling Range, °C	78 - 3,000
Combustibility	Does not Support Combustion
Vapor Pressure, mmHg	No Information

Vapor density	No Information
Specific Gravity (g/cm3)	Not Applicable
Solubility in water	No Information
Partition Coefficient, n-octanol/water	No Information
Auto-Ignition Temperature, °C	No Information
Decomposition temperature, °C	No Information
Viscosity	No Information

9.2. Other information

Volatile organic compounds (VOC) content. 480.32662624

9.2.1. Information with regard to physical hazard classes

No Information

9.2.2. Other safety characteristics

Evaporation rate No Information Available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable.

10.2. Chemical stability

Stable under recommended storage conditions. Risk of ignition. To avoid thermal decomposition, do not overheat. Keep away from open flames, hot surfaces and sources of ignition.

10.3. Possibility of hazardous reactions

None known based on information supplied.

10.4. Conditions to avoid

Excessive heat. Storage near to reactive materials. Take precautionary measures against static discharges. Direct sources of heat.

10.5. Incompatible materials

Reducing agents. Risk of explosion if heated under confinement. Vapors are flammable. May form explosive mixtures in air. Oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity.

Based on available data, the classification criteria are not met.

Product Information

The product itself has not been tested
Data on individual components are tabulated below

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral)	N.R.
ATEmix (dermal)	N.R.
ATEmix (inhalation-vapor)	212.93 mg/l

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
1330-20-7	Xylene	3500 mg/kg Rat	>4350 mg/kg Rabbit	N.R.
13463-67-7	Titanium dioxide	N.R.	N.R.	N.R.
78-83-1	ISOBUTYL ALCOHOL	2460 mg/kg Rat	3400 mg/kg Rabbit	>18.18 mg/L Rat
64-17-5	Ethanol	7060 mg/kg Rat	N.R.	116.9 mg/L, 133.8 mg/L Rat
108-88-3	Toluene	2600 mg/kg Rat	12000 mg/kg Rabbit	N.R.
108-65-6	2-Methoxy-1-methylethyl acetate	N.R.	N.R.	N.R.
112-34-5	2-(2-BUTOXYETHOXY)ETHANOL	5660 mg/kg Rat	2700 mg/kg Rabbit	N.R.
64742-95-6	Solvent naphtha (petroleum), light aromatic	8400	N.R.	N.R.
67-56-1	METHANOL	6200 mg/kg Rat	15840 mg/kg Rabbit	22500 ppm Rat
108-83-8	2,6-Dimethylheptan-4-one	5750 mg/kg Rat	2002	>2300 ppm Rat

50-00-0	Formaldehyde	100 mg/kg Rat	>2000 mg/kg Rat	<463 ppm Rat
108-31-6	Maleic Anhydride	235 mg/kg Rat	2620 mg/kg Rabbit	0.16 mg/L Rat

Skin corrosion/irritation.

May cause sensitization of susceptible persons. May cause allergic skin reaction. May cause sensitization by skin contact. Irritating to skin. May cause irritation. May cause skin irritation. SKIN IRRITANT.

Eye damage/irritation.

Causes serious eye damage.

Germ cell mutagenicity.

Substances which should be regarded as being mutagenic to man.

Carcinogenicity.

This product contains a known or suspected carcinogen. Contains a known or suspected carcinogen.

11.2. Information on other hazards

Endocrine disrupting properties

N.A.

Other information.

N.A.

SECTION 12: Ecological information

12.1. Toxicity

12.74% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Ecotoxicity effects.

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia.
Xylene 1330-20-7	N.D.	LC50 96 h Pimephales promelas 13.4 mg/L, LC50 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L, LC50 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L, LC50 96 h Lepomis macrochirus 13.1 - 16.5 mg/L, LC50 96 h Lepomis macrochirus 19 mg/L, LC50 96 h Lepomis macrochirus 7.711 - 9.591 mg/L, LC50 96 h Pimephales promelas 23.53 - 29.97 mg/L, LC50 96 h Cyprinus carpio 780 mg/L, LC50 96 h Cyprinus carpio >780 mg/L, LC50 96 h Poecilia reticulata 30.26 - 40.	EC50 48 h water flea 3.82 mg/L, LC50 48 h Gammarus lacustris 0.6 mg/L
Titanium dioxide 13463-67-7	N.D.	N.D.	N.D.
ISOBUTYL ALCOHOL 78-83-1	N.D.	LC50 96 h Pimephales promelas 375 mg/L, LC50 96 h Pimephales promelas 1370 - 1670 mg/L, LC50 96 h Lepomis macrochirus 1480 - 1730 mg/L, LC50 96 h Oncorhynchus mykiss 1120 - 1520 mg/L	EC50 48 h Daphnia magna 1300 mg/L, EC50 48 h Daphnia magna 1070 - 1933 mg/L
Ethanol 64-17-5	N.D.	LC50 96 h Oncorhynchus mykiss 12.0 - 16.0 mL/L, LC50 96 h Pimephales promelas >100 mg/L, LC50 96 h Pimephales promelas 13400 - 15100 mg/L	LC50 48 h Daphnia magna 9268 - 14221 mg/L, EC50 48 h Daphnia magna 2 mg/L

Toluene 108-88-3	EC50 96 h Pseudokirchneriella subcapitata >433 mg/L, EC50 72 h Pseudokirchneriella subcapitata 12.5 mg/L	LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L, LC50 96 h Pimephales promelas 12.6 mg/L, LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L, LC50 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L, LC50 96 h Oncorhynchus mykiss 5.8 mg/L, LC50 96 h Lepomis macrochirus 11.0 - 15.0 mg/L, LC50 96 h Oryzias latipes 54 mg/L, LC50 96 h Poecilia reticulata 28.2 mg/L, LC50 96 h Poecilia reticulata 50.87 - 70.34 mg/L	EC50 48 h Daphnia magna 5.46 - 9.83 mg/L, EC50 48 h Daphnia magna 11.5 mg/L
2-Methoxy-1-methylethyl acetate 108-65-6	N.D.	LC50 96 h Pimephales promelas 161 mg/L	EC50 48 h Daphnia magna >500 mg/L
2-(2-BUTOXYETHOXY) ETHANOL 112-34-5	EC50 96 h Desmodesmus subspicatus >100 mg/L	LC50 96 h Lepomis macrochirus 1300 mg/L	EC50 48 h Daphnia magna >100 mg/L
Solvent naphtha (petroleum), light aromatic 64742-95-6	N.D.	LC50 96 h Oncorhynchus mykiss 9.22 mg/L	EC50 48 h Daphnia magna 6.14 mg/L
METHANOL 67-56-1	N.D.	LC50 96 h Pimephales promelas 28200 mg/L, LC50 96 h Pimephales promelas >100 mg/L, LC50 96 h Oncorhynchus mykiss 19500 - 20700 mg/L, LC50 96 h Oncorhynchus mykiss 18 - 20 mL/L, LC50 96 h Lepomis macrochirus 13500 - 17600 mg/L	N.D.
2,6-Dimethylheptan-4-one 108-83-8	EC50 96 h Pseudokirchneriella subcapitata 100 mg/L	LC50 96 h Oncorhynchus mykiss 140 mg/L	N.D.
Formaldehyde 50-00-0	N.D.	LC50 96 h Pimephales promelas 22.6 - 25.7 mg/L, LC50 96 h Lepomis macrochirus 1510 µg/L, LC50 96 h Brachydanio rerio 41 mg/L, LC50 96 h Oncorhynchus mykiss 0.032 - 0.226 mL/L, LC50 96 h Oncorhynchus mykiss 100 - 136 mg/L, LC50 96 h Pimephales promelas 23.2 - 29.7 mg/L	LC50 48 h Daphnia magna 2 mg/L, EC50 48 h Daphnia magna 11.3 - 18 mg/L
Maleic Anhydride 108-31-6	EC50 72 h Desmodesmus subspicatus 29 mg/L	LC50 96 h Oncorhynchus mykiss 75 mg/L	N.D.

12.2. Persistence and degradability

No data are available on the product itself

12.3. Bioaccumulative potential

Discharge into the environment must be avoided.

CAS-No.	Chemical Name	Bio. Conc. Factor (BCF)	Octanol-water par. Coeff (KOW)
1330-20-7	Xylene	N.I.	2.77 - 3.15
13463-67-7	Titanium dioxide	N.I.	N.I.
78-83-1	ISOBUTYL ALCOHOL	N.I.	1
64-17-5	Ethanol	N.I.	-0.35
108-88-3	Toluene	N.I.	2.73
108-65-6	2-Methoxy-1-methylethyl acetate	N.I.	1.2
112-34-5	2-(2-BUTOXYETHOXY)ETHANOL	N.I.	1
64742-95-6	Solvent naphtha (petroleum), light aromatic	N.I.	N.I.
67-56-1	METHANOL	N.I.	-0.77
108-83-8	2,6-Dimethylheptan-4-one	N.I.	3.71
50-00-0	Formaldehyde	N.I.	0.35
108-31-6	Maleic Anhydride	N.I.	-2.36, -2.78, -2.68

12.4. Mobility in soil

Mobility in soil.

No information available

12.5. Results of PBT and vPvB assessment

No data are available on the product itself

12.6. Endocrine disrupting properties

No information available

12.7. Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues / unused products.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Dispose of contents/container to an approved waste disposal plant.

Contaminated packaging.

Do not re-use empty containers.

Other information.

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.

SECTION 14: Transport information

ADR

14.1. UN number or ID number	1263
14.2. UN proper shipping name	Paint Related Material
14.3. Transport hazard class(es)	3
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	No Information

IMDG

14.1. UN number or ID number	1263
14.2. UN proper shipping name	Paint Related Material
14.3. Transport hazard class(es)	3
14.4. Packing group	II
14.5 Marine Pollutant	No.
Environmental hazards	No.
14.6. Special precautions for user	No Information
14.7. Maritime transport in bulk according to IMO instruments	

No Information

IATA

14.1. UN number or ID number	1263
14.2. UN proper shipping name	Paint Related Material
14.3. Transport hazard class(es)	3
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	No Information

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information.

French table of occupational diseases

CAS-No.	Chemical Name	French table of occupational diseases
78-83-1	ISOBUTYL ALCOHOL	RG 84
64-17-5	Ethanol	RG 84
108-65-6	2-Methoxy-1-methylethyl acetate	RG 84
112-34-5	2-(2-BUTOXYETHOXY)ETHANOL	RG 84
64742-95-6	Solvent naphtha (petroleum), light aromatic	RG 84
67-56-1	METHANOL	RG 84
108-83-8	2,6-Dimethylheptan-4-one	RG 84
50-00-0	Formaldehyde	RG 43
108-31-6	Maleic Anhydride	RG 66

European Union.

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Persistent Organic Pollutants

Not applicable

Authorizations and/or restrictions on use:

CAS-No.	Chemical Name	Substance subject to authorization per REACH Annex XIV	Restricted substance per REACH Annex XVII
1330-20-7	Xylene	No.	Yes.
13463-67-7	Titanium dioxide	No.	Yes.
78-83-1	ISOBUTYL ALCOHOL	No.	Yes.
108-88-3	Toluene	No.	Yes.
112-34-5	2-(2-BUTOXYETHOXY)ETHANOL	No.	Yes.
64742-95-6	Solvent naphtha (petroleum), light aromatic	No.	Yes.
67-56-1	METHANOL	No.	Yes.
50-00-0	Formaldehyde	No.	Yes.
108-31-6	Maleic Anhydride	No.	Yes.

EU Substances of Very High Concern

None

International Inventories.

TSCA	Contains Non Listed Components
DSL	Contains Non Listed Components

EINECS/ELINCS	Contains Non Listed Components
ENCS	Contains Non Listed Components
IECSC	Contains Non Listed Components
KECI	Contains Non Listed Components
PICCS	Contains Non Listed Components
AIIC	Contains Non Listed Components
NZIoC	Contains Non Listed Components

TSCA	United States Toxic Substances Control Act Section 8(b) Inventory.
DSL	Canadian Domestic Substances List.
EINECS/ELINCS	European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.
ENCS	Japan Existing and New Chemical Substances.
IECSC	China Inventory of Existing Chemical Substances.
KECL	Korean Existing and Evaluated Chemical Substances.
PICCS	Philippines Inventory of Chemicals and Chemical Substances.
AIIC	Australian Inventory of Industrial Chemicals.
NZIoC	New Zealand Inventory of Chemicals.

15.2. Chemical safety assessment

No.

SECTION 16: Other information

Revision Date 6/27/2023

Indication of changes: Commission Regulation (EU) 2020/878: amending Annex II by introducing specific requirements regarding nanoforms of substances, adapting to the 6th and 7th revision of the GHS, and adding requirements regarding the Unique Formula Identifier (as set by Annex VIII to Regulation (EC) 1272/2008), endocrine disrupting properties, specific concentration limits, M-factors and acute toxicity estimates.

Legend.

N.D.	No data available.
N.I.	No information available.
N.A.	Not Applicable.
N.R.	Not relevant.

This safety datasheet complies with the requirements of Regulation (EC) No. 2020/878

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.