Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product identifier.	FMP2
Product name.	FASTMATCH PATINA BASE
UFI	No Information

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use.	Industrial Wood Coating
Uses advised against.	Professional Use Only

1.3. Details of the supplier of the safety data sheet

Supplier.	Morrells Woodfinishes Ltd John F Kennedy Drive Bluebell Industrial Estate Dublin 12 D12 AW84 Tel: 00 353 1450 5095 EMail: enquires@morrells.co.uk
1.4. Emergency telephone number	Chemtrec: +1-800-424-9300 USA Chemtrec: +1 703-527-3887 ex-USA 24 hrs./day, 7 days/week
Europe	112
Austria	+43 1 406 43 43
Belgium	Poison center (BE): +32 70 245 245
Denmark	Poison Control Hotline (DK): +45 82 12 12 12
Finland	Poison Information Centre (FI):+358 9 471 977
France	ORFILA (FR): + 01 45 42 59 59
Germany	Poison Center Berlin (DE): +49 030 30686 790 |par Poison Center Nord: +49 551 19240 (24h available English / German)
Ireland	National Poisons Information Centre (IE): +353 1 8379964 / + 353 1 8092566
Iceland	+354 543 2222
Italy	Poison Center, Milan (IT): +39 02 6610 1029
Luxembourg	112
Netherlands	National Poisons Information Center (NL): +31 88 755 8000 (NB: this service is only available to health professionals)
Norway	Poisons Information (NO):+ 47 22 591300
Portugal	Poison Information Center (PT): +351 21 330 3284
Spain	Poison Information Service (ES): +34 91 562 04 20
Sweden	Poisons Information Center (SV):+46 8 33 12 31
Switzerland	Poison Center: Tel 145; +41 44 251 51 51
United Kingdom	111 / 0300 020 0155

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flammable Liquid, category 2
STOT, single exposure, category 3, RTI
STOT, single exposure, category 3, NE
Eye Irritation, category 2A
Skin Sensitizer, category 1
Skin drying or cracking

2.2. Label elements

Signal Word

Danger

Hazardous ingredients which must be listed on the label
Not Applicable

Possible Hazards
18.0% of the mixture consists of ingredient(s) of unknown toxicity
18.0% of the mixture consists of ingredient(s) of unknown acute inhalation toxicity

GHS HAZARD STATEMENTS

H319	Causes serious eye irritation.
H225	Highly flammable liquid and vapour.
EUH066	Repeated exposure may cause skin dryness or cracking.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.

GHS SDS PRECAUTIONARY STATEMENTS

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P262	Do not get in eyes, on skin, or on clothing.
P264	Wash contaminated skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use carbon dioxide to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with national regulations.

2.3. Other hazards

EMERGENCY OVERVIEW: No Information

SECTION 3: Composition/information on ingredients

3.1. Substances

This product is a mixture. Health hazard information is based on its components.

3.2. Mixtures

Chemical Name	CAS-No.	EC No.	Wt. %
Isopropyl alcohol	67-63-0	200-661-7	>=30 - <50
Ethyl Acetate	141-78-6	205-500-4	>=20 - <30
ACETONE	67-64-1	200-662-2	>=10 - <20
N-Butyl Acetate	123-86-4	204-658-1	>=5 - <10
Amorphous silixon dioxide	112926-00-8	No Information	>=5 - <10
2,6-Dimethylheptan-4-one	108-83-8	203-620-1	<1
Maleic Anhydride	108-31-6	203-571-6	<0.1

Chemical Name	Classification (1272/2008/EC)	Specific Conc. Limits, M-factors and ATEs
Isopropyl alcohol	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 RTI (H335) STOT SE 3 NE (H336)	ATE oral (mg/kg): 4710 - 5840 mg/kg Rat ATE dermal (mg/kg): 4059 mg/kg Rabbit ATE inhalation - vapor (mg/l/4h): N.R. ATE inhalation - dust/mist (mg/l/4h): N.R.
Ethyl Acetate	EUH066 Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 RTI (H335) STOT SE 3 NE (H336)	ATE oral (mg/kg): 5620 mg/kg Rat ATE dermal (mg/kg): >18000 mg/kg Rabbit ATE inhalation - vapor (mg/l/4h): N.R. ATE inhalation - dust/mist (mg/l/4h): N.R.
ACETONE	EUH066 Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 RTI (H335) STOT SE 3 NE (H336)	ATE oral (mg/kg): 5800 mg/kg Rat ATE dermal (mg/kg): >15700 mg/kg Rabbit ATE inhalation - vapor (mg/l/4h): 50.1 mg/L Rat
N-Butyl Acetate	EUH066 Flam. Liq. 3 (H226) STOT SE 3 RTI (H335) STOT SE 3 NE (H336) Aquatic Chronic 3 (H412)	ATE oral (mg/kg): 10768 mg/kg Rat ATE dermal (mg/kg): >17600 mg/kg Rabbit ATE inhalation - vapor (mg/l/4h): 21 mg/l ATE inhalation - dust/mist (mg/l/4h): N.R.
Amorphous silixon dioxide	Not classified	ATE oral (mg/kg): >20000 mg/kg Rat
2,6-Dimethylheptan-4-one	Flam. Liq. 3 (H226) Acute Tox. 3 Inhalation (H331) STOT SE 3 RTI (H335)	ATE oral (mg/kg): 5750 mg/kg Rat ATE dermal (mg/kg): 2002 ATE inhalation - vapor (mg/l/4h): N.R. ATE inhalation - dust/mist (mg/l/4h): N.R.
Maleic Anhydride	EUH071 Acute Tox. 3 Oral (H301) Skin Corr. 1B (H314) Skin Sens. 1A (H317) Acute Tox. 2 Inhalation (H330) Resp. Sens. 1 (H334) STOT RE 1 (H372)	ATE oral (mg/kg): 235 mg/kg Rat ATE dermal (mg/kg): 2620 mg/kg Rabbit ATE inhalation - dust/mist (mg/l/4h): 0.16 mg/L Rat

For the full text of the H-Statements mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice.

Show this safety data sheet to the doctor in attendance. Do not get in eyes, on skin, or on clothing. May cause allergic skin reaction. Do not delay care and transport of a seriously injured person. Effects should disappear after individual has been exposed to fresh air for approximately 10 minutes. Remove and isolate contaminated clothing and shoes. Consult a physician. Do not breathe dust. Move out of dangerous area. Use personal protective equipment. Remove all sources of ignition. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin. See section 8 for more information. Ensure adequate ventilation.

Inhalation.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Keep victim warm and quiet. If unconscious place in recovery position and seek medical advice. Artificial respiration and/or oxygen may be necessary. Administer oxygen if breathing is difficult. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a doctor immediately if allergic signs, particularly in the respiratory tract, are observed. Get medical attention if symptoms occur.

Skin contact.

Take off contaminated clothing and shoes immediately. Allergic symptoms may develop within 12 hours after exposure. In the case of skin irritation or allergic reactions see a physician. Wash off immediately with soap and plenty of water for at least 15 minutes. Do not remove clothing if adhering to skin. Wash contaminated clothing before reuse. Thoroughly clean shoes before reuse.

Eye contact.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. May produce an allergic reaction. Do not rub affected area. Call a physician if irritation develops or persists.

Ingestion.

Rinse mouth. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. Allergic symptoms may develop within 12 hours after exposure. Call a poison control center or doctor for treatment advice.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms.

Hives. Itching. Rashes. May cause allergic skin reaction. Drowsiness. Dizziness. Skin irritation. Eye irritation. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician.

Treat symptomatically. May cause sensitization of susceptible persons. Effects of contact or inhalation may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media.

Use:. Dry chemical. Carbon dioxide (CO_2). Water spray or fog. Alcohol-resistant foam. Move containers from fire area if you can do it without risk.

Extinguishing media which shall not be used for safety reasons.

Do not use a solid water stream as it may scatter and spread fire. Water may be ineffective.

5.2. Special hazards arising from the substance or mixture

The product causes irritation of eyes, skin and mucous membranes. Flammable. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Will be easily ignited by heat, sparks or flames. Product is or contains a sensitizer. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cool drums with water spray. Fire will produce dense black smoke containing hazardous combustion products (see section 10). Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Container may explode in heat of fire.

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.Keep away from sources of ignition. Prevent fire fighting water from entering surface water or groundwater. Cool containers with spray water from a safe distance. Never use welding or cutting torch on or near container (even empty) because product may ignite explosively.Cool closed containers exposed to fire with water spray.
Pay attention to flashback. Refer to protective measures listed in sections 7 and 8.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions.

Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. Pay attention to flashback. All equipment used when handling the product must be grounded. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stop leak if you can do it without risk. Avoid contact with skin, eyes and inhalation of vapors. A vapor suppressing foam may be used to reduce vapors. Wash thoroughly after handling. Contaminated surfaces will be extremely slippery. Refer to protective measures listed in sections 7 and 8. Do not breathe dust. Wear appropriate respiratory protection and protective clothing as described in Section VIII.

Advice for emergency responders.

Pay attention to flashback. Refer to protective measures listed in sections 7 and 8.

6.2. Environmental precautions

Do not allow material to contaminate ground water system. Should not be released into the environment. Prevent entry into waterways, sewers, basements or confined areas. Prevent spreading of vapors through sewers, ventilation systems and confined areas. Dispose of contents/container to an approved waste disposal plant. See Section 12 for additional Ecological information. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Try to prevent the material from entering drains or water courses. Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for Containment.

Soak up with inert absorbent material. Place into closed container and store in a safe location to await disposal. Wash the spill area with soap and water. Change contaminated clothing and launder before re-use. Wear proper personal protective clothing and equipment.

Methods for cleaning up.

No Information

Other information.

All equipment used when handling the product must be grounded. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate the area. Use personal protective equipment as required.

6.4. Reference to other sections

See Section 8, 13 for additional information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling.

Use spark-proof tools and explosion-proof equipment. Wear personal protective equipment. Remove and wash contaminated clothing before re-use. Take precautionary measures against static discharges. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation at machinery. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Use only in area provided with appropriate exhaust ventilation. Wash thoroughly after handling. Never pierce, drill, grind, cut, saw or weld any empty container. Provide sufficient air exchange and/or exhaust in work rooms. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Keep product and empty container away from heat and sources of ignition. Electrical equipment should be protected to the appropriate standard. Keep container closed when not in use. Ground and bond containers when transferring material.

Hygiene measures.

Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Handle in accordance with good industrial hygiene and safety practice. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin, eyes and clothing. Wash hands before breaks and at the end of workday. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions.

Keep in a bunded area. Keep in properly labeled containers. Keep container tightly closed. Keep in an area equipped with sprinklers. Keep out of the reach of children. Store in accordance with the particular national regulations. Store in accordance with local regulations. Ensure all equipment is electrically grounded before beginning transfer operations. Use spark-proof tools and explosion-proof equipment. Keep locked up or in an area accessible only to qualified or authorized persons. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Store between 41 and 77 °F (5 - 25° C) in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.3. Specific end use(s)

Specific use(s).

No Information

Exposure scenario.

No Information Available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limit Values

Chemical Name	Austria	Belgium	Denmark	European Union.	Finland	France
Isopropyl alcohol 67-63-0	STEL: 800 ppm STEL: 2000 mg/m3 TWA: 200 ppm TWA: 500 mg/m3	STEL: 400 ppm STEL: 1000 mg/m3 TWA: 200 ppm TWA: 500 mg/m3	TWA: 200 ppm TWA: 490 mg/m3	N.D.	STEL: 250 ppm STEL: 620 mg/m3 TWA: 200 ppm TWA: 500 mg/m3	STEL: 400 ppm STEL: 980 mg/m3
Ethyl Acetate 141-78-6	STEL: 400 ppm STEL: 1468 mg/m3 TWA: 200 ppm TWA: 734 mg/m3	STEL: 400 ppm STEL: 1468 mg/m3 TWA: 200 ppm TWA: 734 mg/m3	TWA: 150 ppm TWA: 540 mg/m3	STEL: 1468 mg/m3 STEL: 400 ppm TWA: 734 mg/m3 TWA: 200 ppm	STEL: 400 ppm STEL: 1470 mg/m3 TWA: 200 ppm TWA: 730 mg/m3	STEL: 400 ppm STEL: 1468 mg/m3 TWA: 200 ppm TWA: 734 mg/m3

Chemical Name	Austria	Belgium	Denmark	European Union.	Finland	France
ACETONE 67-64-1	STEL: 2000 ppm STEL: 4800 mg/m3 TWA: 500 ppm TWA: 1200 mg/m3	STEL: 492 ppm STEL: 1187 mg/m3 TWA: 246 ppm TWA: 594 mg/m3	TWA: 250 ppm TWA: 600 mg/m3	TWA: 500 ppm TWA: 1210 mg/m3	STEL: 630 ppm STEL: 1500 mg/m3 TWA: 500 ppm TWA: 1200 mg/m3	STEL: 1000 ppm STEL: 2420 mg/m3 TWA: 500 ppm TWA: 1210 mg/m3
N-Butyl Acetate 123-86-4	STEL: 100 ppm STEL: 480 mg/m3 TWA: 50 ppm TWA: 241 mg/m3	STEL: 150 ppm STEL: 712 mg/m3 TWA: 50 ppm TWA: 238 mg/m3	TWA: 50 ppm TWA: 241 mg/m3	N.D.	STEL: 150 ppm STEL: 725 mg/m3 TWA: 50 ppm TWA: 240 mg/m3	STEL: 150 ppm STEL: 723 mg/m3 TWA: 50 ppm TWA: 241 mg/m3
Amorphous silixon dioxide 112926-00-8	TWA: 4 mg/m3	TWA: 10 mg/m3	N.D.	N.D.	TWA: 5 mg/m3	N.D.
2,6-Dimethylheptan-4-one 108-83-8	TWA: 50 ppm TWA: 290 mg/m3	TWA: 25 ppm TWA: 147 mg/m3	TWA: 25 ppm TWA: 150 mg/m3	N.D.	STEL: 40 ppm STEL: 240 mg/m3 TWA: 25 ppm TWA: 150 mg/m3	TWA: 25 ppm TWA: 250 mg/m3
Maleic Anhydride 108-31-6	STEL: 0.2 ppm STEL: 0.8 mg/m3 TWA: 0.1 ppm TWA: 0.4 mg/m3	TWA: 0.0025 ppm TWA: 0.01 mg/m3	TWA: 0.1 ppm TWA: 0.4 mg/m3	N.D.	TWA: 0.1 ppm TWA: 0.41 mg/m3	STEL: 1 mg/m3

Chemical Name	Germany	Iceland	Ireland	Italy	Luxembourg	Netherlands
Isopropyl alcohol 67-63-0	STEL: 400 ppm STEL: 1000 mg/m3 TWA: 200 ppm TWA: 500 mg/m3	TWA: 200 ppm TWA: 490 mg/m3	STEL: 400 ppm TWA: 200 ppm	N.D.	N.D.	N.D.
Ethyl Acetate 141-78-6	STEL: 400 ppm STEL: 1500 mg/m3 TWA: 200 ppm TWA: 750 mg/m3	TWA: 150 ppm TWA: 540 mg/m3	STEL: 1468 mg/m3 STEL: 400 ppm TWA: 734 mg/m3 TWA: 200 ppm	STEL: 1468 mg/m3 STEL: 400 ppm TWA: 734 mg/m3 TWA: 200 ppm	STEL: 1468 mg/m3 STEL: 400 ppm TWA: 734 mg/m3 TWA: 200 ppm	STEL: 400 ppm STEL: 1468 mg/m3 TWA: 200 ppm TWA: 734 mg/m3
ACETONE 67-64-1	STEL: 1000 ppm STEL: 2400 mg/m3 TWA: 500 ppm TWA: 1200 mg/m3	TWA: 250 ppm TWA: 600 mg/m3	STEL: 1500 ppm STEL: 3630 mg/m3 TWA: 500 ppm TWA: 1210 mg/m3	TWA: 500 ppm TWA: 1210 mg/m3	TWA: 500 ppm TWA: 1210 mg/m3	STEL: 1 ppm STEL: 2420 mg/m3 TWA: 500 ppm TWA: 1210 mg/m3
N-Butyl Acetate 123-86-4	STEL: 200 ppm STEL: 960 mg/m3 TWA: 100 ppm TWA: 480 mg/m3	STEL: 150 ppm STEL: 723 mg/m3 TWA: 50 ppm TWA: 241 mg/m3	STEL: 150 ppm STEL: 723 mg/m3	STEL: 723 mg/m3 STEL: 150 ppm TWA: 241 mg/m3 TWA: 50 ppm	STEL: 723 mg/m3 STEL: 150 ppm TWA: 241 mg/m3 TWA: 50 ppm	STEL: 150 ppm STEL: 723 mg/m3 TWA: 50 ppm TWA: 241 mg/m3
Amorphous silixon dioxide 112926-00-8	STEL: 0.16 mg/m3 TWA: 0.02 mg/m3	N.D.	N.D.	N.D.	N.D.	N.D.
2,6-Dimethylheptan-4-one 108-83-8	N.D.	TWA: 25 ppm TWA: 150 mg/m3	STEL: 75 ppm STEL: 450 mg/m3 TWA: 25 ppm TWA: 150 mg/m3	N.D.	N.D.	N.D.
Maleic Anhydride 108-31-6	STEL: 0.02 ppm STEL: 0.081 mg/m3 TWA: 0.02 ppm TWA: 0.081 mg/m3	TWA: 0.1 ppm TWA: 0.4 mg/m3	STEL: 0.03 ppm TWA: 0.01 ppm	N.D.	N.D.	N.D.

Chemical Name	Norway	Portugal	Spain	Sweden	Switzerland	United Kingdom
Isopropyl alcohol 67-63-0	STEL: 150 ppm STEL: 306.25 mg/m3 TWA: 100 ppm TWA: 245 mg/m3	STEL: 400 ppm TWA: 200 ppm	STEL: 400 ppm STEL: 1000 mg/m3 TWA: 200 ppm TWA: 500 mg/m3	STEL: 250 ppm STEL: 600 mg/m3 TWA: 150 ppm TWA: 350 mg/m3	STEL: 400 ppm STEL: 1000 mg/m3 TWA: 200 ppm TWA: 500 mg/m3	STEL: 500 ppm STEL: 1250 mg/m3 TWA: 400 ppm TWA: 999 mg/m3
Ethyl Acetate 141-78-6	STEL: 400 ppm STEL: 1468 mg/m3 TWA: 200 ppm TWA: 734 mg/m3	STEL: 1468 mg/m3 STEL: 400 ppm TWA: 200 ppm TWA: 734 mg/m3	STEL: 400 ppm STEL: 1468 mg/m3 TWA: 200 ppm TWA: 734 mg/m3	STEL: 300 ppm STEL: 1100 mg/m3 TWA: 150 ppm TWA: 550 mg/m3	STEL: 400 ppm STEL: 1460 mg/m3 TWA: 200 ppm TWA: 730 mg/m3	STEL: 1468 mg/m3 STEL: 400 ppm TWA: 734 mg/m3 TWA: 200 ppm

Chemical Name	Norway	Portugal	Spain	Sweden	Switzerland	United Kingdom
ACETONE 67-64-1	STEL: 156.25 ppm STEL: 368.75 mg/m3 TWA: 125 ppm TWA: 295 mg/m3	STEL: 750 ppm TWA: 500 ppm TWA: 1210 mg/m3	TWA: 500 ppm TWA: 1210 mg/m3	STEL: 500 ppm STEL: 1200 mg/m3 TWA: 250 ppm TWA: 600 mg/m3	STEL: 1000 ppm STEL: 2400 mg/m3 TWA: 500 ppm TWA: 1200 mg/m3	STEL: 1500 ppm STEL: 3620 mg/m3 TWA: 500 ppm TWA: 1210 mg/m3
N-Butyl Acetate 123-86-4	STEL: 723 mg/m3 STEL: 150 ppm TWA: 241 mg/m3 TWA: 50 ppm	STEL: 150 ppm STEL: 723 mg/m3 TWA: 50 ppm TWA: 241 mg/m3	STEL: 150 ppm STEL: 723 mg/m3 TWA: 50 ppm TWA: 241 mg/m3	STEL: 150 ppm STEL: 723 mg/m3 TWA: 50 ppm TWA: 241 mg/m3	STEL: 150 ppm STEL: 720 mg/m3 TWA: 50 ppm TWA: 240 mg/m3	STEL: 200 ppm STEL: 966 mg/m3 TWA: 150 ppm TWA: 724 mg/m3
Amorphous silixon dioxide 112926-00-8	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
2,6-Dimethylheptan-4-one 108-83-8	STEL: 30 ppm STEL: 150 mg/m3 TWA: 20 ppm TWA: 120 mg/m3	TWA: 25 ppm	TWA: 25 ppm TWA: 148 mg/m3	N.D.	TWA: 25 ppm TWA: 150 mg/m3	STEL: 75 ppm STEL: 444 mg/m3 TWA: 25 ppm TWA: 148 mg/m3
Maleic Anhydride 108-31-6	STEL: 0.6 ppm STEL: 2.4 mg/m3 TWA: 0.2 ppm TWA: 0.8 mg/m3	TWA: 0.01 mg/m3	TWA: 0.1 ppm TWA: 0.4 mg/m3	STEL: 0.1 ppm STEL: 0.4 mg/m3 TWA: 0.05 ppm TWA: 0.2 mg/m3	STEL: 0.1 ppm STEL: 0.4 mg/m3 TWA: 0.1 ppm TWA: 0.4 mg/m3	STEL: 3 mg/m3 TWA: 1 mg/m3

TWA: Time weighted average
STEL: Short term exposure limit.

EU - REACH (1906/2006) Registration Data - Derived No Effect Levels (DNELs)

Chemical Name	CAS Number	DNEL
Isopropyl alcohol	67-63-0	general population oral systemic effects long term exposure 26 mg/kg bw/day DNEL (200-661-7); general population inhalation systemic effects long term exposure 89 mg/m3 DNEL (200-661-7); general population dermal systemic effects long term exposure 319 mg/kg bw/day DNEL (200-661-7); workers inhalation systemic effects long term exposure 500 mg/m3 DNEL (200-661-7); workers dermal systemic effects long term exposure 888 mg/kg bw/day DNEL (200-661-7); workers inhalation systemic effects acute/short term exposure 1000 mg/m3 DNEL (200-661-7); general population inhalation systemic effects acute/short term exposure 178 mg/m3 DNEL (200-661-7); general population oral systemic effects acute/short term exposure 51 mg/kg bw/day DNEL
Ethyl Acetate	141-78-6	general population oral systemic effects long term exposure 4.5 mg/kg bw/day DNEL (205-500-4); general population dermal systemic effects long term exposure 37 mg/kg bw/day DNEL (205-500-4); workers dermal systemic effects long term exposure 63 mg/kg bw/day DNEL (205-500-4); general population inhalation systemic effects long term exposure 367 mg/m3 DNEL (205-500-4); general population inhalation local effects long term exposure 367 mg/m3 DNEL (205-500-4); workers inhalation systemic effects long term exposure 734 mg/m3 DNEL (205-500-4); workers inhalation local effects long term exposure 734 mg/m3 DNEL (205-500-4); general population inhalation systemic effects acute/short term exposure 734 mg/m3 DNEL (205-500-4); general population inhalation local effects acute/short term exposure 734 mg/m3 DNEL (205-500-4); workers inhalation systemic effects acute/short term exposure 1468 mg/m3 DNEL (205-500-4); workers inhalation local effects acute/short term exposure 1468 mg/m3 DNEL (205-500-4)
ACETONE	67-64-1	general population dermal systemic effects long term exposure 62 mg/kg bw/day DNEL (200-662-2); general population oral systemic effects long term exposure 62 mg/kg bw/day DNEL (200-662-2); workers dermal systemic effects long term exposure 186 mg/kg bw/day DNEL (200-662-2); general population inhalation systemic effects long term exposure 200 mg/m3 DNEL (200-662-2); workers inhalation systemic effects long term exposure 1210 mg/m3 DNEL (200-662-2); workers inhalation local effects acute/short term exposure 2420 mg/m3 DNEL (200-662-2)

Chemical Name	CAS Number	DNEL
2,6-Dimethylheptan-4-one	108-83-8	workers dermal systemic effects long term exposure 7.7 mg/kg bw/day DNEL (203-620-1); workers inhalation systemic effects long term exposure 53 mg/m3 DNEL (203-620-1)

EU - REACH (1906/2006) Registration Data - Predicted No Effect Concentrations (PNECs)

Chemical Name	CAS Number	PNEC
Ethyl Acetate	141-78-6	0.24 mg/L PNEC (freshwater, 205-500-4); 0.024 mg/L PNEC (marine water, 205-500-4); 1.65 mg/L PNEC (freshwater (intermittent releases), 205-500-4); 0.2 g/kg food PNEC (food chain, 205-500-4); 1.15 mg/kg sediment dw PNEC (sediment (freshwater), 205-500-4); 0.115 mg/kg sediment dw PNEC (sediment (marine water), 205-500-4); 650 mg/L PNEC (sewage treatment, 205-500-4); 0.148 mg/kg soil dw PNEC (soil, 205-500-4)
ACETONE	67-64-1	10.6 mg/L PNEC (freshwater, 200-662-2); 1.06 mg/L PNEC (marine water, 200-662-2); 21 mg/L PNEC (freshwater (intermittent releases), 200-662-2); 30.4 mg/kg sediment dw PNEC (sediment (freshwater), 200-662-2); 3.04 mg/kg sediment dw PNEC (sediment (marine water), 200-662-2); 100 mg/L PNEC (sewage treatment, 200-662-2); 29.5 mg/kg soil dw PNEC (soil, 200-662-2)
N-Butyl Acetate	123-86-4	0.18 mg/L PNEC (freshwater, 204-658-1); 0.018 mg/L PNEC (marine water, 204-658-1); 0.36 mg/L PNEC (freshwater (intermittent releases), 204-658-1); 0.981 mg/kg sediment dw PNEC (sediment (freshwater), 204-658-1); 0.0981 mg/kg sediment dw PNEC (sediment (marine water), 204-658-1); 35.6 mg/L PNEC (sewage treatment, 204-658-1); 0.0903 mg/kg soil dw PNEC (soil, 204-658-1)
2,6-Dimethylheptan-4-one	108-83-8	0.03 mg/L PNEC (freshwater, 203-620-1); 0.003 mg/L PNEC (marine water, 203-620-1); 0.3 mg/L PNEC (freshwater (intermittent releases), 203-620-1); 0.46 mg/kg sediment dw PNEC (sediment (freshwater), 203-620-1); 0.046 mg/kg sediment dw PNEC (sediment (marine water), 203-620-1); 2.55 mg/L PNEC (sewage treatment, 203-620-1); 0.0746 mg/kg soil dw PNEC (soil, 203-620-1)

EU - REACH (1906/2006) Article 59(1) - Candidate Substances of Very High Concern (SVHC)

None

8.2. Exposure controls

Engineering Measures.

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protective equipment.

Eye/Face Protection.

Tightly fitting safety goggles. If splashes are likely to occur, wear:. Face-shield.

Skin and body protection.

No special protective equipment required. Solvent-resistant gloves. Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Follow the skin protection plan. Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Flame retardant antistatic protective clothing. Antistatic boots.

The selected protective gloves have to satisfy the specifications of EU Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Respiratory protection.

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Preferably a compressed airline breathing apparatus. Breathing apparatus with filter. Respirator with filter for organic vapor. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Environmental Exposure Controls.

No Information

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	No Information
Colour	Clear
Odour	No Information
Odour Threshold	No Information
pH	No Information
Melting Point, °C	No Information
Flash Point, °C	-17
Boiling Range, °C	56 - 1,355
Combustibility	Does not Support Combustion
Vapor Pressure, mmHg	No Information
Vapor density	No Information
Specific Gravity (g/cm3)	Not Applicable
Solubility in water	No Information
Partition Coefficient, n-octanol/water	No Information
Auto-Ignition Temperature, °C	No Information
Decomposition temperature, °C	No Information
Viscosity	No Information

9.2. Other information

Volatile organic compounds (VOC) content.	782.507937629

9.2.1. Information with regard to physical hazard classes

No Information

9.2.2. Other safety characteristics

Evaporation rate	No Information Available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable.

10.2. Chemical stability

Stable under recommended storage conditions. Risk of ignition. To avoid thermal decomposition, do not overheat. Keep away from open flames, hot surfaces and sources of ignition.

10.3. Possibility of hazardous reactions

None known based on information supplied.

10.4. Conditions to avoid

Excessive heat. Storage near to reactive materials. Take precautionary measures against static discharges. Direct sources of heat.

10.5. Incompatible materials

Reducing agents. Risk of explosion if heated under confinement. Vapors are flammable. May form explosive mixtures in air. Oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity.

Based on available data, the classification criteria are not met.

Product Information

The product itself has not been tested
Data on individual components are tabulated below

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral)	N.R.
ATEmix (dermal)	>5000 mg/kg

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
67-63-0	Isopropyl alcohol	4710 - 5840 mg/kg Rat	4059 mg/kg Rabbit	N.R.
141-78-6	Ethyl Acetate	5620 mg/kg Rat	>18000 mg/kg Rabbit	N.R.
67-64-1	ACETONE	5800 mg/kg Rat	>15700 mg/kg Rabbit	50.1 mg/L Rat
123-86-4	N-Butyl Acetate	10768 mg/kg Rat	>17600 mg/kg Rabbit	21 mg/l
112926-00-8	Amorphous silixon dioxide	>20000 mg/kg Rat	N.R.	N.R.
108-83-8	2,6-Dimethylheptan-4-one	5750 mg/kg Rat	2002	>2300 ppm Rat
108-31-6	Maleic Anhydride	235 mg/kg Rat	2620 mg/kg Rabbit	0.16 mg/L Rat

Skin corrosion/irritation.

May cause sensitization of susceptible persons. May cause allergic skin reaction. May cause sensitization by skin contact. Repeated exposure may cause skin dryness or cracking. Mild skin irritation. May cause irritation.

Eye damage/irritation.

Irritating to eyes. Causes moderate eye irritation.

Respiratory or skin sensitization.

May be harmful if inhaled. May cause irritation. May cause drowsiness.

Specific target organ systemic toxicity (single exposure).

Vapors may cause drowsiness and dizziness.

11.2. Information on other hazards

Endocrine disrupting properties

N.A.

Other information.

N.A.

SECTION 12: Ecological information

12.1. Toxicity

7.89% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Ecotoxicity effects.

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia.
Isopropyl alcohol 67-63-0	EC50 96 h Desmodesmus subspicatus >1000 mg/L, EC50 72 h Desmodesmus subspicatus >1000 mg/L	LC50 96 h Pimephales promelas 9640 mg/L, LC50 96 h Pimephales promelas 11130 mg/L, LC50 96 h Lepomis macrochirus >1400000 µg/L	EC50 48 h Daphnia magna 13299 mg/L
Ethyl Acetate 141-78-6	N.D.	LC50 96 h Pimephales promelas 220 - 250 mg/L, LC50 96 h Oncorhynchus mykiss 484 mg/L, LC50 96 h Oncorhynchus mykiss 352 - 500 mg/L	EC50 48 h Daphnia magna 560 mg/L
ACETONE 67-64-1	N.D.	LC50 96 h Oncorhynchus mykiss 4.74 - 6.33 mL/L, LC50 96 h Pimephales promelas 6210 - 8120 mg/L, LC50 96 h Lepomis macrochirus 8300 mg/L	EC50 48 h Daphnia magna 10294 - 17704 mg/L, EC50 48 h Daphnia magna 12600 - 12700 mg/L

N-Butyl Acetate 123-86-4	EC50 72 h Desmodesmus subspicatus 674.7 mg/L	LC50 96 h Lepomis macrochirus 100 mg/L, LC50 96 h Pimephales promelas 17 - 19 mg/L	N.D.
Amorphous silixon dioxide 112926-00-8	N.D.	N.D.	N.D.
2,6-Dimethylheptan-4-one 108-83-8	EC50 96 h Pseudokirchneriella subcapitata 100 mg/L	LC50 96 h Oncorhynchus mykiss 140 mg/L	N.D.
Maleic Anhydride 108-31-6	EC50 72 h Desmodesmus subspicatus 29 mg/L	LC50 96 h Oncorhynchus mykiss 75 mg/L	N.D.

12.2. Persistence and degradability
No data are available on the product itself

12.3. Bioaccumulative potential
No Information

CAS-No.	Chemical Name	Bio. Conc. Factor (BCF)	Octanol-water par. Coeff (KOW)
67-63-0	Isopropyl alcohol	N.I.	0.05
141-78-6	Ethyl Acetate	N.I.	0.73
67-64-1	ACETONE	N.I.	-0.24
123-86-4	N-Butyl Acetate	N.I.	1.81, 2.3
112926-00-8	Amorphous silixon dioxide	N.I.	N.I.
108-83-8	2,6-Dimethylheptan-4-one	N.I.	3.71
108-31-6	Maleic Anhydride	N.I.	-2.36, -2.78, -2.68

12.4. Mobility in soil
Mobility in soil.
No information available

12.5. Results of PBT and vPvB assessment
No data are available on the product itself

12.6. Endocrine disrupting properties
No information available

12.7. Other adverse effects
No information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods
Waste from residues / unused products.
Disposal should be in accordance with applicable regional, national and local laws and regulations. Dispose of contents/container to an approved waste disposal plant.

Contaminated packaging.
Do not re-use empty containers.

Other information.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.

SECTION 14: Transport information

ADR

14.1. UN number or ID number	1263
14.2. UN proper shipping name	Paint Related Material
14.3. Transport hazard class(es)	3
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	No Information

IMDG

14.1. UN number or ID number	1263
14.2. UN proper shipping name	Paint Related Material

14.3. Transport hazard class(es)	3
14.4. Packing group	II
14.5 Marine Pollutant	No.
Environmental hazards	No.
14.6. Special precautions for user	No Information
14.7. Maritime transport in bulk according to IMO instruments	No Information

IATA

14.1. UN number or ID number	1263
14.2. UN proper shipping name	Paint Related Material
14.3. Transport hazard class(es)	3
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	No Information

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information.

French table of occupational diseases

CAS-No.	Chemical Name	French table of occupational diseases
67-63-0	Isopropyl alcohol	RG 84
141-78-6	Ethyl Acetate	RG 84
67-64-1	ACETONE	RG 84
123-86-4	N-Butyl Acetate	RG 84
108-83-8	2,6-Dimethylheptan-4-one	RG 84
108-31-6	Maleic Anhydride	RG 66

European Union.

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Persistent Organic Pollutants

Not applicable

Authorizations and/or restrictions on use:

CAS-No.	Chemical Name	Substance subject to authorization per REACH Annex XIV	Restricted substance per REACH Annex XVII
67-63-0	Isopropyl alcohol	No.	Yes.
141-78-6	Ethyl Acetate	No.	Yes.
67-64-1	ACETONE	No.	Yes.
108-31-6	Maleic Anhydride	No.	Yes.

EU Substances of Very High Concern

None

International Inventories.

TSCA	Contains Non Listed Components
DSL	Contains Non Listed Components
EINECS/ELINCS	Contains Non Listed Components
ENCS	Contains Non Listed Components
IECSC	Contains Non Listed Components
KECI	

	Contains Non Listed Components
PICCS	Contains Non Listed Components
AIIC	Contains Non Listed Components
NZIoC	Contains Non Listed Components

TSCA	United States Toxic Substances Control Act Section 8(b) Inventory.
DSL	Canadian Domestic Substances List.
EINECS/ELINCS	European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.
ENCS	Japan Existing and New Chemical Substances.
IECSC	China Inventory of Existing Chemical Substances.
KECL	Korean Existing and Evaluated Chemical Substances.
PICCS	Philippines Inventory of Chemicals and Chemical Substances.
AIIC	Australian Inventory of Industrial Chemicals.
NZIoC	New Zealand Inventory of Chemicals.

15.2. Chemical safety assessment

No.

SECTION 16: Other information

Revision Date 3/24/2025

Indication of changes: Commission Regulation (EU) 2020/878: amending Annex II by introducing specific requirements regarding nanoforms of substances, adapting to the 6th and 7th revision of the GHS, and adding requirements regarding the Unique Formula Identifier (as set by Annex VIII to Regulation (EC) 1272/2008), endocrine disrupting properties, specific concentration limits, M-factors and acute toxicity estimates.

Legend.

N.D.	No data available.
N.I.	No information available.
N.A.	Not Applicable.
N.R.	Not relevant.

This safety datasheet complies with the requirements of Regulation (EC) No. 2020/878

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.