

MPR-Hammer head fasteners


zinc lamella coating

Field of application

- For time-saving, efficient attachment of pipe clamps to MPR-Support channels
- For indoor and outdoor use

Advantages

- Easy and fast assembly in the rail slot
- Lateral adjustment at any time, allows perfect alignment of the pipeline after installation
- Various lengths and thread diameters can be combined within the same channel
- Interlocking threaded plate for secure positive connection in the rail slot of the MPR-Support channels




| For support channels | Connecting thread M | Length [mm] | Usable thread length L [mm] | Part no. | Sales unit | Pack unit |
|--|---------------------|-------------|-----------------------------|----------|------------|-----------|
| 41/21/2.0, 41/41/2.0, 41/41/2.5, 41/62/2.5, 41/42/2.0, 41/82/2.0, 41/124/2.5 | M8 | 35 | 10 | 154193 | 25 | pieces |
| | | 40 | 15 | 154194 | | |
| | | 50 | 25 | 154195 | | |
| | | 80 | 55 | 154196 | | |
| | | 100 | 75 | 154197 | | |
| | M10 | 35 | 8 | 154198 | | |
| | | 40 | 13 | 154199 | | |
| | | 55 | 28 | 154200 | | |
| | | 60 | 33 | 154201 | | |
| | | 80 | 53 | 154202 | | |
| 41/21/2.0, 41/41/2.0, 41/41/2.5, 41/62/2.5, 41/82/2.0, 41/124/2.5 | M12 | 100 | 73 | 154203 | | |
| | | 40 | 9 | 154204 | 10 | |
| | | 55 | 24 | 154205 | | |
| | | 60 | 29 | 154206 | | |
| 80 | 49 | 154207 | | | | |
| 100 | 69 | 154208 | | | | |
| 41/41/2.0, 41/41/2.5, 41/62/2.5, 41/82/2.0, 41/124/2.5 | M16 | 65 | 30 | 154209 | | |
| | | 100 | 65 | 154210 | | |



MPR-Hammer head fasteners

zinc lamella coating



| For support channels Material thickness [mm] | MPR-Hammer head fasteners | | |
|--|---------------------------|--|------------------------------------|
| | Connecting thread | Max. recommended tensile load Fz [N] | For a tightening torque of [Nm] |
| 2.0 | M8 | 4.500 | 9 |
| | M10 | | 17 |
| | M12 | | 29 |
| | M16 | | |
| 2.5 | M8 | 5.000 | 9 |
| | M10 | | 17 |
| | M12 | | 29 |
| | M16 | | |

